

32" CHANNEL DRAIN FLAT GRATE ANTI-ENTRAPMENT SUCTION OUTLET COVER AND PVC THREE-PORT MANUFACTURED SUMP

VGB Series

The AquaStar line of suction outlet covers, compliant with the Virginia Graeme-Baker Pool and Spa Safety Act (ANSI/APSP 16-2011 and NSF/ANSI 50-2009a)

FEATURES

For single or multiple drain use (see installation instructions for plumbing, hydrostatic valve/drain pipe and single or multi-pump connections)

Single

Floor: 316 GPM at 3.9 fps Wall: 208 GPM at 2.6 fps

Floor/wall: 122 GPM at 1.5 fps Floor/wall: 80.7 GPM at 1.0 fps

25.9 square inch opening

#316 stainless steel screws

PVC sump (standard)

Manufactured from superior UV-resistant engineered polymers

Three ports: bottom $2\frac{1}{2}$ " OD, 2" ID S/S; inside 2" threaded FPT; two 2" threaded plugs included

All components meet or exceed ANSI/ APSP 16-2011 and NSF/ANSI 50-2009a national standards and ASTM G154 UV testing exposure

Disposable plastic pre-gunite/plaster insert keeps debris out and retains sump shape during construction

Does not require use of transition glue


Replace every five years from the date of installation

4 per case

Unblockable!



New waterstop feature



With sump (concrete pools)
Part # 32CDFLxxx

STANDARD COLORS

32CDFL101 – White

32CDFL102 – Black

32CDFL103 – Light Gray

32CDFL104 - Blue

32CDFL105 – Dark Gray


32CDFL108 – Tan


Also available as sump only p/n 32CDPxxx 4 per case


Also available cover only without sump/frame p/n 32CDFLNFxxx

40 per case

VGB 2008 Compliant







- 1. 32" three-port manufactured sump bucket
- 2. 32" channel drain, cover, flat
- 3. 2" NPT plug, qty 2
- 4. 32" channel drain, plaster shield
- 5. #10 x 3/4" flat head Phillips Type A screw, 316 ss, qty 16