

COLOR SELECTION - PAVERS AND COPING









PRODUCT DATA SHEET

REGION

EAST COAST

SERIES

STEPLOCK®

SHELLOCK®

The original seashell paver®.

Seashells mixed into the paver and then honed to exposed the beauty of each individual seashell in a sleek smooth surface, creating a very comfortable paver to walk on barefoot. The nonslippery polished surface is smooth and impeccably fashionable.

The Shellock® collection is part of our Steplock® Line, exclusively designed for pedestrian applications.

APPLICATIONS



Designed for use in pedestrian applications including patios, swimming pool decks, walkways, stepping stones as well as architectural and decorative uses such as raised walls, fountains, benches and planters.

FINISHES



POLISHED

COPING & SPECIALTY PIECES

NOMINAL SIZES (in). THICKNESS: 1-5/8

One Sided 4x8, 4x12, 4x16, 24x12, 12x12, 16x8, 16x16, 24x24

Two Sided 4x12, 4x16, 24x12, 12x12, 16x16, 24x24

Three Sided 4x16, 12x12, 16x16, 24x24 Four Sided 12x12, 16x16, 24x24 Adjacent 12x12, 16x16, 24x24

Remodeling 4x12 with 3"drop-face, 4" drop-face, 5" drop-face.

Precut one sided 4x8, 4x12 Precut two sided 4x12, 4x16

PAVER AND PAVING SLABS

SIZES & PACKAGING

NOMINAL SIZE (in)	ACTUAL DIMENSIONS (mm)	SQ FT PER PALLET	WEIGHT PER PALLET
8 x 8 x 1-5/8*	200 x 200 x 40	160 SQ FT	2,870 LBS
8 x 12 x 1-5/8	200 x 300 x 40	160 SQ FT	2,870 LBS
12 x 12 x 1-5/8	300 x 300 x 40	180 SQ FT	3,255 LBS
12 x 24 x 1-5/8*	300 x 600 x 40	120 SQ FT	2,160 LBS
16 x 16 x 1-5/8*	400 x 400 x 40	160 SQ FT	2,870 LBS
24 x 24 x 1-5/8	600 x 600 x 40	120 SQ FT	2,160 LBS
4 x 8 x 1-5/8 ⁽⁴⁾	200 x 200 x 40	75 SQ FT	1,361 LBS

STRAIGHT RELAXED-EDGE COPING

NOMINAL SIZES (in). THICKNESS: 1-5/8"

One Sided 4x12, 12x12, 24x12 in Ivory and Tan. One Sided 24x12 in Silver Sam.

CUSTOM COLORS

Custom colors available typically for minimum quantities of 10,000 square feet.

- NOTES

 1. The Shellock® collection has natural shells embedded at different distances from the surface of the pave.

 1. The Shellock® collection has natural shells embedded at different distances from the surface of the shells are expected to come loose from or coping, and then polished. Therefore, a small percentage of the shells are expected to come loose from the surface and edges of the tile. This occurrence will diminish over a short span of time and in no way will effect the strength of the products.
- 2. Pavers should be installed from several pallets at a time to maintain the best color consistency.
- Due to processes required to manufacture, package, deliver, unpack, install and compact the products, small chipping can be expected.

 The 4x8 border pavers are machine cut and not dimensionally consistent. Artistic Paver Mfg. recommends
- these pavers should be used strictly as border material, therefore, not recommended for field material.
- The product images in our catalogs, brochures, or shown on monitor screens give a general indication of color for a preliminary selection. We recommend you also view current product samples and look at actual finished projects before making your final decision.

EAST COAST PLANT

MAIN OFFICE

120 NE 179th St. North Miami Beach, FL 33162 (305) 653-7283



WEST COAST PLANT