

Color Hardener and Antique Release Color Chart



Prior to using Brickform products, refer to the current TIS and SDS available at www.brickform.com or by using the QR codes below.

COLOR HARDENER is an engineered blend, used to color the surface of new concrete. Color Hardener is manufactured with the finest UV-resistant pigments and premium aggregates available. Color Hardener is designed to work with imprinting tools to produce clear, sharp impressions that enhance the finished appearance of any new hardscape. When properly applied and worked into newly placed, fresh concrete, Color Hardener forms a colored concrete surface that is abrasion- and impact-resistant. Color Hardener is available in 42 standard colors and has an approximate coverage rate of 90 to 120 ft² per 60 lb pail. Coverage rate will vary depending on timing, color, and application technique. This chart represents 24 of the 42 colors available only.

ANTIQUE RELEASE is a hydrophobic colored powder that helps prevent Brickform imprinting tools from sticking during the stamping process. Antique Release is made from a finely ground formula that works with polyurethane texturing mats to create a beautifully antiqued and textured concrete surface. Antique Release forms a waterproof barrier that enables the stamping tool to be removed without concrete buildup on the stamp. During the stamping process, Antique Release

is pressed into the concrete surface, creating a secondary coloring effect once washed off and sealed. Antique Release is available in 42 standard colors and has a coverage rate of 800-1000 ft² per 30 lb pail depending on application.

ANTIQUE-IT is a water-soluble antiquing agent designed to impart a secondary color or highlight to hardened stamped concrete or textured overlays. Antique-It is easy to apply, dries fast, and provides a durable color that closely resembles the look of antiquing release powder. Antique-It is available in 42 standard colors. Coverage Rate: 2000-3000 ft² per 3 lb. container.



WARRANTY • These products are not intended for public use and are intended for use by licensed contractors and installers, experienced and trained in the use of these products. They are warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of these products, therefore, no warranty, expressed or implied, is or can be made either as to the affects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability. CAUTIONS • KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the appropriate Technical Data Sheet, Safety Data Sheet and Warranty. DO NOT TAKE INTERNALLY. Avoid contact with skin and eyes. Use only with a NIOSH approved respirator when using these products. Installation guidelines available at www.brickform.com.

Brickform Color Hardener, Antique Release and Antique-It are available in 42 standard colors. This color chart is a representation only and does not quarantee that the final color will be an exact match. Texturing or finishing techniques such as brooming or troweling, the use of sealers, and slight color drifts in raw materials will produce variations of the colors. Brickform strongly recommends a representative job sample for each product.

BRICKFORM®, A Division of Solomon Colors, Inc. 4050 Color Plant Road, Springfield, IL 62702 Customer Service: 800-483-9628

www.brickform.com

An Employee-Owned Company . Made in USA

Distributed	by:	