

- Complies with American National Standard Z358.1-2009 as a supplemental eyewash only
- 5-Gallon Pressurized Tank
- Eyewash or Highly Visible Yellow-Colored Hose Spray
- Universal Identification Sign and Inspection Tag Included
- Full, One-Year Warranty

## Specifications

Ideal for providing emergency protection in areas where permanent water supply is not available. Supplements permanent eyewash unit installations. Five-gallon pressure tank is constructed of stainless steel. 25½" (648mm) high and 8½" (216mm) outside diameter. Weighs 4 lbs. empty and 51 lbs. full. Tire filler valve with 0–160 PSI air gauge. 8' hand-held hose spray or eyewash assembly has chrome-plated metal parts. Flow from hose maintained approximately 2½ minutes. Hose burst strength is 450 PSI. Hand-held hose sprayhead contains an antimicrobial agent to protect the sprayhead.

## Standard Equipment

### 5-Gallon Tank


Stainless steel pressure tank has built-in carrying handles and resilient bottom. Tire filler valve with 0–160 PSI air gauge. Pressure relief valve prevents accidental over pressurization.

### Hand-Held Hose Spray (S19-670 only)

8' (2438mm) yellow hose spray with hand-held squeeze-type valve, full-size spray nozzle, and hose clamp. All metal parts are chrome-plated. Flow maintained for approximately 1½ minutes.

### Eyewash (S19-671 only)

Twin chrome-plated brass, soft flow eyewash heads with automatic flow control stay-open valve. Protective dust covers are included. Hand operated by a large, highly visible stainless steel push handle. Flow from eyewash maintained approximately 8 minutes.

 *Personal eyewash equipment does not meet the criteria of plumbed or self-contained eyewash equipment. Personal eyewashes support plumbed or self-contained units but shall not replace them.*

Model	Description
<input type="checkbox"/> S19-670	5-Gal. Portable, Pressurized Unit w/ Drench Hose Only
<input type="checkbox"/> S19-671	5-Gal. Portable, Pressurized Unit w/ Eyewash Only

