



BOSS[®] 804 Pool & Spa Silicone

TYPICAL PROPERTIES

Tensile	225
Tack-Free Time	30 min.
Full Cure	24 hours
Shore A Hardness	15
Specific Gravity	1.02
Extrusion Rate	400 g/min.
Slump	Nil
Elongation	600%
Service Temperature	-40°F to 325°F
Application Temperature	-35°F to 140°F

*Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Accumetric, LLC



DESCRIPTION

BOSS[®] 804 Pool & Spa Silicone is a premium quality silicone sealant specially formulated for grouting ceramic tile. **BOSS[®] 804** is a one-part, neutral cure, mildew resistant, silicone sealant that has very little odor and cleans up easily with warm water.

FEATURES

- **Waterproof / weatherproof**
- **Mildew resistant**
- **Non-sag formula**
- **Good adhesion to ceramic and porcelain tile, natural stone, polycarbonate pool and spa and lighting covers**
- **VOC compliant in all 50 states**

COLORS

BOSS[®] 804 Pool & Spa Silicone is available in white. Custom orders available upon request.

ESTIMATING REQUIREMENTS

Silicone grout usage as measured in square feet per cartridge

Tile Size	Coverage (approximate)
1" x 1"	3 square feet
2" x 2"	3.5 square feet
3" x 3"	4 square feet

HOW TO USE

1. Clean and dry surfaces. Remove any soap film, oil or grease from surfaces.
2. Cut tip off cartridge and screw on nozzle. Cut nozzle at 45° angle. Insert cartridge into standard caulking gun.
3. Apply sealant by pushing sealant ahead of nozzle.
4. The paste-like consistency makes it easy to work: a spatula or wooden paddle can be used for tooling the surface.
5. Clean surface with warm water and paper towels.

CLEAN UP

Uncured sealant can be easily removed using a solvent such as alcohol or acetone. For an environmental and health friendlier choice use BOSS® Biggie Wipes. If the sealant is cured it must be removed mechanically by cutting and scraping.

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use with adequate ventilation. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Material Safety Data Sheet (MSDS).

PACKAGING

BOSS® 804 Pool & Spa Silicone is available in standard caulking cartridges and 4.5 gallon pails.

SHIPPING LIMITATIONS

None.

Reactive VOC 27 g/L (<3% wt)

STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), **BOSS® 804** Pool & Spa Silicone has a shelf life of 12 months from date of shipment. In Countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright with the nozzle tip pointed upwards. DO NOT stack cartons on their side. **NEVER** stack cartons more than 8 high. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building.

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-warranty: Because the storage, handling and application of the material is beyond Accumetric's control, we can accept no liability for the results obtained. Accumetric's sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Accumetric will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.

MADE IN U.S.A.

BOSS® PRODUCTS

Accumetric, LLC
350 Ring Road
Elizabethtown,
Kentucky 42701 USA
800-928-BOSS(2677)
TEL (270)769-3385
FAX (270)765-2412
Outside U.S.
TEL +1(270)769-3385
FAX +1(270)765-2412

Accumetric Asia Pacific, LTD
18 Kitpanit Bldg. 5th Floor
#502 Patpong Road
Suriyawong, Bangrak
Bangkok, 10500 Thailand
TEL (662)634-3060
FAX (662)634-3066

www.bossproducts.com