



S9TS01 • HTS201 BEIGE
24x24 in 60x60 cm



S9TS09 • HTS209 NOCE
24x24 in 60x60 cm

Special Pieces



S8TS01G • Step / HTS201 BEIGE
12x24 in 30x60 cm



S8TS09G • Step / HTS209 NOCE
12x24 in 30x60 cm



S8TS01C • Pool Coping with full round edge / HTS201 BEIGE
12x24 in 30x60 cm



S8TS09C • Pool Coping with full round edge / HTS209 NOCE
12x24 in 30x60 cm



THICKNESS

0.79"
20 mm



FREEZE / THAW

RESISTANT
ASTM C 1026



WATER ABSORPTION

~0,1%
ASTM C 373



RECOMMENDED USE



CHEMICAL/STAIN RESISTANCE

Class: A
ASTM C 650
Class: A
ASTM C 1378



BREAKING STRENGTH

≥3400 lbs.
ASTM C 648



SLIP RESISTANCE


≥0.60
ANSI 137.1 (DCOF)

PACKAGING 24x24 in



Pcs.	66
Sq.Ft.	255.75
Lbs.	2380

SHADE VARIATION



Del Conca USA, Inc. - 155 Del Conca Way - Loudon, TN 37774 - USA
Tel 865.657.3550 - Fax 865.657.3554
www.delconcausa.com - sales@delconcausa.com

