


SPECIFICATIONS		
	EC-10	EC-20
¹ NUMBER OF OZONE MODULES	2	4
VOLTAGE	120-240 V	120-240 V
AMPERAGE	0.10 A MAX	0.20 A MAX
ENCLOSURE MATERIAL	POWDERCOATED GALVANNEALED STEEL	POWDERCOATED GALVANNEALED STEEL
ENCLOSURE RATING	NEMA 3, IP54	NEMA 3, IP54
OPERATING TEMPERATURE	35-129 °F	35-129 °F
APPROVALS	CLASSIFIED UL 139927	CLASSIFIED UL 139927

ALL DIMENSIONS IN INCHES		APPROVALS:	DATE:	PROPERTY OF DEL OZONE THIS DOCUMENT AND THE DATA DISCLOSED HEREIN IS PROPRIETARY. IT IS NOT TO BE REPRODUCED, USED, OR OTHERWISE DISCLOSED IN WHOLE, OR IN PART, TO ANYONE, WITHOUT WRITTEN CONSENT FROM DEL OZONE.
TOLERANCES:		DRAWN:	4/8/2014	
.x ± .1		ENGR. APPR:	4/9/2014	
.xx ± .02		CHECKED:		
.xxx ± .010		Q.A. APPR:		
ANGLES ±1°				
MATERIAL:				
FINISH:				

		TITLE: SPECIFICATION_SHEET, EC-20, EC-10	
INTERPRET DRAWING PER ANSI Y14.5-1994	SCALE: 1:3	SIZE: B	DWG. NO: 4-2155-01
DO NOT SCALE DRAWING		REV. A	SHEET: 1 OF 1

ZONE	REV.	INITIAL RELEASE	DESCRIPTION	ECN	DATE
			REVISIONS		



D
C
B
A
B FORMAT REV A