

**Product Family**  
**3" CladLite® Pads**  
**Equipment Pads**



**Description**

**1636-3**

CladLite® Equipment Pads provide the strength and durability customers demand in an easy to install pad. CladLite® Pads are to up 80% lighter than solid concrete but still provide rock solid support for equipment. Once it's set, so are you. CladLite® Pads stay in place and can withstand anything mother nature can throw at them. These pads provide superior resistance to sun, moisture, and freeze-thaw conditions. And the vibration dampening EPS foam core is unaffected by water, soil, fungus or bacteria. The 3 inch thick CladLite® pad is the choice for equipment pads when required by the local building code.

**Features**

- 125 lbs. per 2" diameter foot
- 80% lighter than solid concrete
- Continuous steel reinforcement
- Full foam bottom resists settling and vibration
- Impervious to weather

**Specifications**

**Warranty:**

Limited Lifetime Warranty

**Performance:**

Flawless performance under the 25-cycle regimen specified by ASTM C67

**Chemical Resistance:**

Does not craze, soften, delaminate, or spall when tested per ASTM D2299 with the following:

- R-22 and R-134a
- Compressor oil
- Synthetic canine urine
- Salt solution, 20% by volume

**Foam Core:**

ASTM Type 1 EPS

**Flame Resistance:**

Cladding resists compressor heat and incidental torch contact. Not to be used under heating devices.

STOCK NO	Material	Size	Thickness	Estimated Allowable Load	Weight
1636-3	Concrete/Foam	16 x 36	3 in	70 lbs	48 lbs
2424-3	Concrete/Foam	24 x 24	3 in	173 lbs	42.55 lbs
2436-3	Concrete/Foam	24 x 36	3 in	259 lbs	59.45 lbs
2448-3	Concrete/Foam	24 x 48	3 in	346 lbs	83.45 lbs
2460-3	Concrete/Foam	24 x 60	3 in	431 lbs	105 lbs
2626-3	Concrete/Foam	26 x 26	3 in	205 lbs	49.50 lbs
3030-3	Concrete/Foam	30 x 30	3 in	270 lbs	61.50 lbs
3036-3	Concrete/Foam	30 x 36	3 in	324 lbs	73.05 lbs
3040-3	Concrete/Foam	30 x 40	3 in	360 lbs	94 lbs
3060-3	Concrete/Foam	30 x 60	3 in	540lbs	130 lbs
3143-3	Concrete/Foam	31 x 43	3 in	577 lbs	74 lbs
32-3	Concrete/Foam	Round	3 in	307 lbs	67 lbs
3232-3	Concrete/Foam	32 x 32	3 in	307 lbs	67.7 lbs
3237-3	Concrete/Foam	32 x 37	3 in	355 lbs	73 lbs
3345-3	Concrete/Foam	33 x 45	3 in	413 lbs	99.1 lbs
3636-3	Concrete/Foam	36 x 36	3 in	389 lbs	80.4 lbs
3640-3	Concrete/Foam	36 x 40	3 in	423 lbs	97.2 lbs
3648-3	Concrete/Foam	36 x 48	3 in	518 lbs	109.05 lbs
3650-3	Concrete/Foam	36 x 50	3 in	542 lbs	148 lbs
3660-3	Concrete/Foam	36 x 60	3 in	661 lbs	163 lbs
3678-3	Concrete/Foam	36 x 78	3 in	874 lbs	196 lbs
3842-3	Concrete/Foam	38 x 42	3 in	479 lbs	119.55 lbs
3870-3	Concrete/Foam	38 x 70	3 in	798 lbs	181 lbs
4042-3	Concrete/Foam	40 x 42	3 in	504	158 lbs
4054-3	Concrete/Foam	40 x 54	3 in	648 lbs	167 lbs
4062-3	Concrete/Foam	40 x 62	3 in	745 lbs	167 lbs
4147-3	Concrete/Foam	41 x 47	3 in	560 lbs	155 lbs
4183-3	Concrete/Foam	41 x 83	3 in	1069 lbs	231 lbs
4550-3	Concrete/Foam	45 x 50	3 in	627 lbs	184 lbs
4558-3	Concrete/Foam	45 x 58	3 in	783 lbs	203 lbs
4766-3	Concrete/Foam	47 x 66	3 in	821 lbs	219 lbs
4848-3	Concrete/Foam	48 x 48	3 in	691 lbs	184 lbs
5053-3	Concrete/Foam	50 x 53	3 in	795 lbs	197 lbs
5056-3	Concrete/Foam	50 x 56	3 in	840 lbs	212 lbs
5058-3	Concrete/Foam	50 x 58	3 in	870 lbs	212 lbs
5070-3	Concrete/Foam	50 x 70	3 in	1051 lbs	257 lbs
5252-3	Concrete/Foam	52 x 52	3 in	811 lbs	197 lbs
5557-3	Concrete/Foam	55 x 57	3 in	546 lbs	237 lbs
6067-3	Concrete/Foam	60 x 67	3 in	841 lbs	284 lbs



**Simplify The Way You Work**

6650 Sugarloaf Parkway, Duluth, GA 30097 Phone: 800-955-2222 Fax: 678-542-3700 www.diversitech.com

© 2016 Diversitech Corporation

All rights reserved.

Rev. 4/04/17

Page 1 of 1