



COMMERCIAL

MODELS:

2448KW 24hp, 48" Deck 2454KW 24hp, 54" Deck 2460KW 24hp, 60" Deck

THE SMOOTHEST DRIVING MOWER ON THE MARKET.

The **BlackHawk** is built to redefine your mowing experience with superior value, advanced operator controls, commercial grade components, and unmatched performance.

- Foot-Operated OCDC Our foot-operated OCDC (operator-controlled discharge chute) allows you to keep your hands on the steering levers while closing the discharge chute on the fly.
- **Proven Power –** Equipped with 24 horsepower Kawasaki^{*} FS engines for years of trusted reliability and performance.
- **Robust Deck** Offered in three cutting widths, the BlackHawk deck features a deep 7 gauge shell and **abrasion resistance baffles** to outlast the competition in extreme conditions.
- **Smoothest Steering** The Parker* transmissions offer super smooth steering up to 9 miles per hour in a compact, quiet, and efficient drivetrain.
- **Total Comfort** The padded and over-sized bolstered seat hugs your torso for ultimate comfort.
- **Peer' Turf Xtreme™ Spindles** Maintenance free and constructed of high-strength ductile iron.



OCDC - Foot-operated to keep your hands on the steering levers



Parker' HTE – Smooth steering and 1,000 hour oil change intervals



48", 54", and 60" Decks - Deep 7 gauge shell to tackle deep grass

BlackHawk 2460KW shown*



Hitch Receiver – Class 1 hitch for easier mounting of accessories



PEER' Spindles – Maintenance free with Contamination Exclusion Technology



*Unlimited hour limited warranty, see dealer for complete warranty details

Black Hawk **

	48" Deck	54″ Deck	60" Deck		
Model	2448KW	2454KW	2460KW		
Engine					
Manufacturer	Kawasaki" FS				
Horsepower		24			
Displacement		726cc			
Air-cleaner	2 stage				
Cooling	Air-cooled				
Starter		Electric			
Engine warranty		3-Year			

Drive System				
Dual hydrostatic	Parker [®] HTE			
Ground speed	9 mph			
Parking brake	Integrated in transaxle			
Towing capacity	200 lbs			

Mower Deck					
Deck size	48″	54"	60"		
Acres/hour*	3.4	3.9	4.3		
Cutting height	1" - 5"				
OCDC (operator controlled discharge chute)	Foot-operated (standard)				
Deck height adjustments	Manual lift, 1/4" increments				
Electric lift	Optional				
Deck engagement	Ogura® 150 ft-lbs				
Construction	7 ga formed & welded, Abrasion Resistance Baffles				
Blades	(3) -2.5" x 17.25"	(3) - 2.5" × 19"	(3) - 2.5" x 20.5"		
Blade tip speed (approximate)	18,500 fpm				
Spindles	1.25" effective diameter machined shaft				
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)				
Anti-scalp rollers	4				
Pulleys	7 ga steel d	Vented split 3/8"steel deep groove			

General			
Battery	12 Volt, 350cca		
Digital Display	Tachometer, hour meter, fuel gauge		
Fuel capacity	7 gallons		
Rear tires	23 x 10.5-12 GrassMaster		
Front tires	13 x 6.5-6		
Frame	Welded C-channel, 7 ga formed		
Floor-pan	Removable, steel		
Seat	24" high-back adjustable padded seat w/ armrests		
Springer Forks	Optional accessory		

Dimensions				
Overall height (rollbar down)	50"			
Overall height (rollbar up)	71"			
Overall width (chute down)	63.6″	69.6"	76″	
Overall width (chute up)	49.2"	55.4"	61.9"	
Overall length (rollbar down)	85.8"			
Overall length (rollbar up)	81.3″			
Weight	1104 lbs	1114 lbs	1121 lbs	



(765)-CHOPPER www.dixiechopper.com