BLACKHAWK HP



COMMERCIAL

MODELS:

2454KW 23.5hp, 54" Deck 2460KW 23.5hp, 60" Deck 2660KWE 26hp, 60" Deck 2760KW 27hp, 60" Deck



WHERE COMMERCIAL MEETS COMFORTABLE.

The **BlackHawk HP** provides the superior mowing experience with advanced operator controls, commercial grade components, and best-in-class performance and comfort.

- **Total Comfort** Full suspension seat with padded design provides lateral stability and comfort.
- Foot-Operated OCDC A foot-operated OCDC (operator-controlled discharge chute) allows you to keep your hands on the steering levers while closing the discharge chute on the fly.
- Proven Power Equipped with the industry preferred Kawasaki* FX or FT EFI engines for reliability and performance year after year.
- **Smoothest Steering** The Parker* transmissions offer super smooth steering up to 11 miles per hour in a compact, quiet, and efficient drivetrain.
- **Robust Deck** Offered in two cutting widths (54"and 60"), the BlackHawk HP deck features a deep 7 gauge shell and **abrasion resistance baffles** to outlast the competition in extreme conditions.
- **Peer** * **Turf Xtreme** * **Spindles** Maintenance free and constructed of high-strength ductile iron.



Suspension Seat - Full suspension for ultimate comfort all day long



OCDC - Foot-operated to keep your hands on the steering levers



Parker HTJ - Smooth steering and 1,000 hour oil change intervals



Kawasaki* **Engines -** Reliable power to tackle the toughest jobs



54" and 60" Decks - Deep 7 gauge shell to tackle tough grass with ease



*Unlimited hour limited warranty, see dealer for complete warranty details



	54" Deck		60" Deck	
Model	2454KW	2460KW	2660KWE	2760KW (SS)
Engine				
Manufacturer	Kawasaki* FX		Kawasaki* FT EFI	Kawasaki* FX
Horsepower	23.5		26	27
Displacement	726cc		852cc	
Air-cleaner	4 stage		Vortical Air Filtration	4 stage
Cooling	Air-cooled Air-cooled			
Starter	Electric			
Engine warranty	3-Year			

Drive System			
Dual hydrostatic	Parker HTJ		
Ground speed	10 mph 11 r		
Parking brake	Integrated in transaxle		
Towing capacity	200 lbs		

Mower Deck			
Deck size	54"	60"	
Acres/hour*	4.3	4.8	5.3
Cutting height	1" - 5"		
OCDC (operator controlled discharge chute)	Foot-operated (standard) Optional		Optional
Deck height adjustments	Manual lift, 1/4" increments		
Electric lift	Optional		
Deck engagement	Ogura* 150 ft-lb		
Construction	7 ga formed & welded, Abrasion Resistance Baffles		
Blades	(3) - 2.5" x 19" (3) - 2.5" x 20.5"		
Blade tip speed (approximate)	18,500 fpm		
Spindles	1.25" effective diameter machined shaft		
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)		
Anti-scalp rollers	4		
Pulleys	7 ga vented split steel deep groove		

General				
Battery	12 Volt, 350cca			
Digital Display	Tachometer, hour meter, fuel gauge	hour meter, fuel gauge	Tachometer, hour meter, fuel gauge	
Fuel capacity	7 gallons			
Rear tires	23 x 10.5-12 GrassMaster		24 x 12-12 GrassMaster	
Front tires	13 x 6.5-6			
Frame	Welded C-channel, 7 ga formed			
Floor-pan	Removable, steel			
Seat	Full suspension, adjustable seat w/ armrests			
Springer Forks	Optional accessory		Standard	

Dimensions				
Overall height (rollbar down)	50"		50.5"	
Overall height (rollbar up)	71" 71.5"		71.5"	
Overall width (chute down)	69.6"	76"		
Overall width (chute up)	55.4"	61.9"		
Overall length (rollbar down)	85.8"			
Overall length (rollbar up)	81.3"			
Weight	1132 lbs	1140 lbs	1170 lbs	

