

## COMMERCIAL

## **MODELS:**

3560KW 35hp, 60" Deck 4060VGE 40hp, 60" Deck 3572KW 35hp, 72" Deck 4072VGE 40hp, 72" Deck



## THE ULTIMATE MOWING EXPERIENCE.

The new **Eagle HP** provides the ultimate mowing experience with unmatched combination of speed, power, performance, and comfort.

- **2-Speed Transaxle** Hydro-Gear\* ZT-5400 gives operators speeds up to 18mph for faster ground transportation and increased productivity.
- **Springer Forks** Standard on all Eagle HP models to help absorb bumps and imperfections in the turf creating a smoother ride for the operator.
- **Pure Power –** Equipped with the industry preferred Kawasaki<sup>\*</sup> FX engine or a 40hp Vanguard<sup>\*</sup> Big Block EFI for more power and fuel savings.
- **Robust Deck** Offered in two cutting widths (60"and 72"), the Eagle HP deck features a deep 7 gauge shell and **abrasion resistance baffles** to outlast the competition in extreme conditions.
- **Ultimate Comfort** High-back bolstered design with padded armrests, recline, lumbar, and isolated platform provides the best riding experience.
- **Run-Flat Tires** Flat tires are a problem of the past with run-flat tires standard on the Eagle HP.

HYDRO-GEAR COMMERCIAL

**BIXIE CHOPPE** 



60" CUT

**2-Speed Transaxle –** Speeds up to 18mph for increased productivity



**Suspension Seat –** High back, padded armrests, and isolated platform



60" and 72" Decks - Deep 7 gauge shell to tackle deep grass with ease





**OCDC -** Foot-operated to keep your hands on the steering levers



**Springer Forks –** Help absorb rough terrain and provide smoother ride



\*Unlimited hour limited warranty, see dealer for complete warranty details

## EAGLE HP

	60" Deck		72" Deck		
Model	3560KW	4060VGE	3572KW	4072VGE	
Engine					
Manufacturer	Kawasaki* FX	Vanguard <sup>®</sup> Big Block EFI	Kawasaki* FX	Vanguard <sup>®</sup> Big Block EFI	
Horsepower	35	40	35	40	
Displacement	999cc	993cc	999cc	993cc	
Air-cleaner	4 stage & Turbinator <sup>®</sup> Pre-Cleaner				
Cooling	Air-cooled				
Starter	Electric				
Engine warranty	3-Year				

Drive System	
Dual hydrostatic	Hydro-Gear <sup>®</sup> ZT-5400 w/ 2-Speed
Ground speed	12 mph / 18mph
Parking brake	Integrated in transaxle
Towing capacity	300 lbs (low-speed only)

Mower Deck					
Deck size	60"	72"			
Acres/hour	8.7	10.4			
Cutting height	1" - 5"				
OCDC (operator controlled discharge chute)	Foot-operated (standard)				
Deck height adjustments	Manual lift, 1/4" increments				
Electric lift	Optional				
Deck engagement	Warner <sup>*</sup> 250 ft-lbs				
Construction	7 ga formed & welded, Abrasion Resistance Baffles				
Blades	(3) - 2.5" × 20.5"	(3) - 2.5" 24.5"			
Blade tip speed (approximate)	18,500 fpm				
Spindles	1.25" effective diameter machined shaft				
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)				
Anti-scalp rollers	4				
Pulleys	Vented split 3/8" steel deep groove				

General				
Battery	12 Volt, 350cca			
Digital Display	Hour meter, fuel gauge			
Fuel capacity	10 gallons			
Rear tires	25 x 12-12 GrassMaster			
Front tires	15 x 6-8 (run-flat)			
Frame	Welded C-channel, 7 ga formed			
Floor-pan	Removable, steel			
Seat	High-back, full suspension, lumbar, recline, padded armrests, and isolated platform			
Springer Forks	Standard			

Dimensions							
Overall height (rollbar down)	55″						
Overall height (rollbar up)	78.5″						
Overall width (chute down)	76.9"		89.5″				
Overall width (chute up)	67"		79.6″				
Overall length (rollbar down)	88.6″	90.9″	90.5″	92.8″			
Overall length (rollbar up)	87.1"		90.4				
Weight	1386 lbs		1426 lbs				



(765)-CHOPPER www.dixiechopper.com

\*Acres/hour at top speed and 80% efficient Specifications, while correct at the time of printing, may change without notice. Engine horsepower is provided by the engine manufacturer to be used for comparison only. ©2022 Dixie Chopper. All rights reserved.