Industrial / Chemical Processing Blowers

DR 505 & CP 505

2.0 / 3.0 HP Regenerative Blower

ROTRON®

FEATURES

- · Manufactured in the USA ISO 9001 and NAFTA compliant
- CE compliant Declaration of Conformity on file
- · Maximum flow: 150 SCFM
- · Maximum pressure: 88 IWG
- · Maximum vacuum: 73 IWG
- · Standard motor: 2.0 HP, TEFC
- Cast aluminum blower housing, impeller & cover; cast iron flanges (threaded)
- UL & CSA approved motor with permanently sealed ball bearings
- · Inlet & outlet internal muffling
- · Quiet operation within OSHA standards

MOTOR OPTIONS

- International voltage & frequency (Hz)
- Chemical duty, high efficiency, inverter duty or industry-specific designs
- · Various horsepowers for application-specific needs

BLOWER OPTIONS

- Corrosion resistant surface treatments & sealing options
- Remote drive (motorless) models
- · Slip-on or face flanges for application-specific needs

ACCESSORIES

- · Flowmeters reading in SCFM
- Filters & moisture separators
- · Pressure gauges, vacuum gauges, & relief valves
- · Switches air flow, pressure, vacuum, or temperature
- · External mufflers for additional silencing
- · Air knives (used on blow-off applications)
- Variable frequency drive package





This document is for informational purposes only and should not be considered as a binding description of the products or their performance in all applications. The performance data on this page depicts typical performance under controlled laboratory conditions. AMETEK is not responsible for blowers driven beyond factory specified speed, temperature, pressure, flow or without proper alignment. Actual performance will vary depending on the operating environment and application. AMETEK products are not designed for and should not be used in medical life support applications. AMETEK reserves the right to revise its products without notification. The above characteristics represent standard products. For product designed to meet specific applications, contact AMETEK Technical & Industrial Products Sales department.

