



# SRM-3020 TRIMMER/BRUSHCUTTER

#### **CLASS-LEADING POWER AND PERFORMANCE**

Unique combination of engine size, horsepower and gear ratio provides superior cutting performance. Available in three versions to best meet specific job requirements.



## **PROFESSIONAL HIGHLIGHTS**

#### **POWERFUL 30.5 CC ENGINE WITH 1.8 HORSEPOWER**

#### Hot restart capability

 Engine design inhibits hot air from reaching carburetor for reliable starts

#### Two-stage air filtration

- Large surface area prevents debris from getting into engine
- Extends filter maintenance intervals

#### Speed-Feed® 450 trimmer head

- Improves efficiency with maximum line capacity
- Comes with professional-grade Black Diamond™ line



#### 20" cutting swath

Increases productivity compared to the competition



#### Tool-less air filter cover

- Easier to perform regular air filter cleaning
- Thumbscrew fasteners provide tight seal







## SRM-3020 TRIMMER/BRUSHCUTTER

### FEATURES AND BENEFITS

 30.5 cc high-performance professional-grade engine

Produces 1.8 hp

 Magnesium fan housing Reduces weight

• Over-molded front and rear hand grips Improves operator comfort

1.62:1 gear reduction
 Provides superior cutting performance





Provides the best combination of performance and low vibration



SPECIFICATIONS <sup>†</sup>	ECHO®	ECHO®	ECHO®	ECHO®	<b>Stihl</b> ®	Husqvarna
Model	SRM-3020	SRM-3020T	SRM-3020U	SRM-280	FS 111 R	430LS
Engine (cc)	30.5	30.5	30.5	28.1	31.4	29.5
Power (hp)	1.8	1.8	1.8	1.25	1.4	1.3
Cylinder Plating	Chrome	Chrome	Chrome	Al-Fed	Chrome	Chrome
Piston	2-Ring	2-Ring	2-Ring	1-Ring	2-Ring	2-Ring
Gear Ratio	1.62:1	2.07	1.62:1	1.4	1.33	1.4
Cutting Swath	20"	20"	20"	17"	17"	17"
Fuel Capacity (oz)	24	24	24	21.1	24	23.7
Air Filter	Foam and Pleated	Foam and Pleated	Foam and Pleated	Foam and Felt	Pleated	Felt
Dry Weight (lbs)*	12.1	12.3	13.2	12.3	12.1	11.2
Dry Weight (lbs)**	13.7	13.9	14.8	13.2	-	-

<sup>\*</sup>dry weight without cutting head or shield

<sup>\*\*</sup>dry weight with cutting head and shield