Commercial Weed Stopper

Weed Control • Filter Fabric • Soil Separator

2 oz. Spunbond



AVAILABLE SIZES

Retail Cases

3 x 25

3 X 50	zu per case	45#^
3 x 100	12 per case	55#*
6 x 50	12 per case	55#*
Bulk Rolls		
3 x 250	750 sq. ft.	13#*
4 x 250	1000 sq. ft.	18#*
5 x 250	1250 sq. ft.	22#*
6 x 250	1500 sq. ft.	26#*
8 x 250	2000 sq. ft.	35#*
10 x 250	2500 sq. ft.	43#*
12 x 250	3000 sq. ft.	52#*
15 x 250	3750 sq. ft.	66#*

30 per case

42#*

* Roll sizes & weights may vary. For best results the use of a pre and post emergent herbicide is advised.



WEED CONTROL FABRIC

- Stops approx. 95% of weed growth
- Lets air, water and fertilizer pass through to plant roots
- · Saves you time (no more weeding)
- Permanent when covered from sunlight

FILTER FABRIC

- Wrap around pipe or use behind retaining walls
- Protects native soil and silt from clogging drainage septic systems
- Drainage protection to maintain flow and percolation
- Prolongs life of septic drain fields and drainage pipes

BENEFITS


- · Cuts quickly, no fraying
- Easy to install
- · Available in variety of retail and bulk sizes
- Permanent when covered from sunlight

USE UNDER OR AROUND

- Wooden Decks
- Decorative Stone & Bark
- Retaining Wall Filter Fabric
- . Drainage and Septic Systems
- Annual Vegetable Gardens

^{*} Refer to page 18 for installation instructions





TYPICAL SPECIFICATIONS

Properties	Test Method	2 oz.
Unit Weight (oz/yd²)	ASTM D-3776	2.0
Tensile Strength (lbs)	ASTM D-4632	73
Elongation at Break (%)	ASTM D-4632	>70
Puncture Strength (lbs)	ASTM D-4751	23
A.O.S. (equivalent sieve)	ASTM D-4751	30/40
A.O.S. (mm)		.52
Trap Tear (lbs)	ASTM D-4533	35
Coefficient of		
Permeability (cm/sec)	ASTM D-4491	7 x 10 ⁻²
Flux (gal/ft²/min)	ASTM D-4491	200
Permittivity (sec-1)	ASTM D-4491	3.0
Thickness (mils)	ASTM D-1777	11.5
Material Polypropylene		







6398 W. 74TH ST. • BEDFORD PARK, ILLINOIS 60638 (708) 728-7180 • 1-800-992-0550 • FAX: (708) 728-0482 www.fabriscape.com • e-mail: info@fabriscape.com