



PRODUCT DATA



Paint & Urethane Stripper

(Formerly SOY•Gel™ Paint and Urethane Remover)

Franmar's **BLUE BEAR Paint & Urethane Stripper** is a tried and true stripper, used by consumers for over two decades. Effectively removes multiple layers of paint, varnish, enamel, urethane, other simple coatings, and lead based paint*. Made with soybeans, **Paint & Urethane Stripper** is the choice for a safe, low odor, non-caustic, green coating remover for any DIY project.

**Ideal for lead-based paint removal. The lead becomes encapsulated in the gel, preventing airborne particles and allowing for safe removal. Dispose of in accordance with all existing local, state, and federal ordinances.*

Coverage:

Coverage per square foot varies depending on type and age of coating, number of layers and method of application.

Horizontal: Average coverage is 125 sq ft per gallon (max 200 sq ft per gallon)

Vertical: Average coverage is 75 sq ft per gallon

Test Area:

Due to variances in surfaces and conditions, always test in a small, inconspicuous area before using on complete project.

Application:

Apply a thick layer of **Paint & Urethane Stripper** by pouring, brushing, squeegee, or commercial airless sprayer. Applying too thin will cause **Paint & Urethane Stripper** to dry out before removal is complete. Use a scraper to check if the coating is softened down to the surface. If not, wait longer and recheck. When the coating is completely softened, remove with a scraper.

Clean Up:

Use **BLUE BEAR General Purpose Degreaser** or water and a scrub brush, mop, or power washer to clean remaining thin residue. Remove excess coating(s) and **Paint & Urethane Stripper** before using a power washer for final cleaning. Allow surface to dry before further preparations.

Usage Tips from the Pros:

- For large application areas, use a professional airless sprayer or a 4-stage HVLP sprayer.
- For tough coatings or numerous layers, use a notched 1/2" squeegee or 1/4" gauge rake. Square footage will be greatly reduced.
- When used outdoors, cover with a 2mil or thicker plastic to help keep **Paint & Urethane Stripper** wet and working.

Biodegradable: Meets or exceeds ASTM standards

Precautions: Concrete surfaces may darken with use of **Paint & Urethane Stripper**. Protect plants and vegetation with a plastic drop cloth. Always use care to prevent overspray from getting on surfaces other than the one being prepped or cleaned.

Warnings: May cause skin irritation. May cause eye irritation. May cause respiratory irritation or may cause drowsiness and dizziness. May be harmful if swallowed. This product contains a chemical known to the state of California to cause birth defects or other reproductive harm. Keep out of reach of children.

Flash Point Above 200°F (93.3°C)

pH Level 8.1 pH of 1/10 wt/wt solution in soft water

VOC (Volatile Organic Compounds) 49%, 4.249 lb/g, 509 g/l
California and OTC Compliant

Ingredients: N-Methyl Pyrrolidone, Dibasic Ester LVP, Soy Ester, Proprietary Thickening and Surfactant Blend

Safe for Use On: Concrete, masonry, wood, and metal

Do Not Use On: PVC, drywall, limestone, plastic, veneer, terrazzo tile, or rubber

NON-EMERGENCY

Call: 800.538.5069

www.franmar.com

CHEMICAL EMERGENCY:

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

USA and Canada: 800.242.9300

CCN717946 or +1 703.527.3887

(Collect Calls Accepted)



PO Box 5565
Bloomington IL 61702

Rev. 3/29/2016