
HCP 3000 SERIES PUMPS

HCP 3000 Series pumps are game changers in commercial pump performance and versatility. Engineered for heavy-duty durability, they set a new flow rate standard for the 3" union class. A variety of power options from 2 to 7 HP, including single- or 3-phase and single or variable speed, means you can provide the optimum solution for a wide range of pools, delivering maximum performance without compromising efficiency.



- » First 3" pumps to achieve hydraulic performance of more than 250 gallons per minute at 60' of head [7 HP model], saving more energy than any comparable pump on the market
- » Modern Totally Enclosed Fan Cooled (TEFC) motors in all models provide a higher level of reliability
- » Chemical-resistant Viton® seal for long-term durability
- » Removable, oversized strainer basket reduces daily cleaning and maintenance and can be remotely mounted for increased versatility
- » 3" union connections for simple, drop-in replacement in almost any application
- » 2.7 HP variable-speed version available
- » Available in single- or 3-phase
- » **3-year** limited warranty on VSP model
- » 1-year limited warranty on single-speed models
- » NSF/ANSI Standard 50 Certified







TECHNICAL SPECIFICATIONS

PART NUMBER	RATED HORSEPOWER	VOLTAGE	RATED CURRENT (AMPS)	HZ	CARTON QUANTITY	CARTON WEIGHT (LBS.)	
HCP3020VSP	2.7	230V Single Phase, Variable Speed	10.9	50/60	1	65.0	
HCP30201	2.0	208-230V Single Phase, Single Speed	8.7-7.9	3.7-7.9 50/60		91.0	
HCP30301	3.0	208-230V Single Phase, Single Speed	11.7-11.5	50/60	1	96.0	
HCP30501	5.0	208-230V Single Phase, Single Speed	21.0-20.0	21.0-20.0 60		102.0	
HCP30203	2.0	208-230/460V 3-Phase, Single Speed	7.8-7.6/3.8	50/60	1	91.0	
HCP30203C	2.0	330-575V 3-Phase, Single Speed	7.8-7.6/3.8	50/60	1	91.0	
HCP30303	3.0	208-230/460V 3-Phase, Single Speed	9.2-9.0/4.5	9.2-9.0/4.5 50/60		96.0	
HCP30303C	3.0	330-575V 3-Phase, Single Speed	9.2-9.0/4.5	50/60	1	96.0	
HCP30503	5.0	208-230/460V 3-Phase, Single Speed	13.6-13.2/6.6	50/60	1	102.0	
HCP30503C	5.0	330-575V 3-Phase, Single Speed	13.6-13.2/6.6	50/60	1	102.0	
HCP30703	7.0	230/460V 3-Phase, Single Speed	17.2-8.6	50/60	1	107.0	
HCP30703C	7.0	330-575V 3-Phase, Single Speed	17.2-8.6	50/60	1	107.0	

PERFORMANCE DATA HCP3020VSP PERFORMANCE DATA HCP 3000 SERIES PERFORMANCE DATA 60HZ (SINGLE- AND 3-PHASE MODELS) - 3000 mm - 100 000 April 2000 0000 - ROMERS AND DESCRIPTION - 225,676 MARKED - 100 EW TOTAL MEAD IFT, OF MATTER 50% 4%MIGH. No. Ď. 176 280 225 250 275 300 325 350 375 50. 200 225 250 275 PLEW DIPMO FLOW (OPM)

			PUMP OUTPUT (GPM) VS. TOTAL RESISTANCE TO FL				OW (PER FT OF HEAD)		
PART NUMBER			40	50	60	70	80	90	
SINGLE PHASE	3-PHASE	HP	FLOW RATE (GPM)						
HCP30201	HCP30203	2.0	170	156	140	120	85	_	
HCP30301	HCP30303	3.0	198	185	166	145	115	40	
HCP30501	HCP30503	5.0	232	217	200	179	150	100	
_	HCP30703	7.0	303	285	265	240	210	155	

