

PSR

PUMP START RELAY

Type: **Accessory**

FEATURES

- Three models available to fit your particular application
- NEMA 3R rated locking plastic enclosure rated for outdoor use, weather resistance and security
- 24 VAC flying leads make it quick and easy to wire to controller
- The PSR-22 meets demanding electrical requirements for UL approval, and the PSR-52/-53 contains UL-approved relays
- Warranty period: 2 years



Pump Start Relay

Height: 6½"
Width: 7½"
Depth: 4½"

PUMP START RELAY

Model	Description
PSR-22	Double pole/single throw pump start relay for 120 VAC pumps up to 2 hp or 230 VAC pumps up to 3 hp
PSR-52	Double pole/single throw pump start relay for 120 VAC pumps up to 3 hp or 230 VAC pumps up to 7.5 hp
PSR-53	Triple pole/single throw pump start relay for 120 VAC pumps up to 3 hp, 230 VAC pumps up to 7.5 hp, or 230 VAC pumps up to 10 hp (3 phase)

PUMP START RELAY ELECTRICAL SPECIFICATIONS

Model	Single Phase			3 Phase HP at 230 VAC	Max. Full Load AMPS	Max. Resistive AMPS	Coil VA						
	HP at 120 VAC	HP at 230 VAC	HP at 230 VAC				INRUSH		AMPS		HOLDING		
							50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz
PSR-22	2*	3*	N/A	30	40	33	30	1.38	1.25	8	6.5	0.33	0.27
PSR-52	3	7.5	N/A	40	50	65	60	2.71	2.50	7.5	5	0.31	0.21
PSR-53	3	7.5	10	40	50	65	60	2.71	2.50	7.5	5	0.31	0.21

Note:

* Approximate power

PSRB

PUMP START RELAY BOOSTER

FEATURES

- Solves long distance pump start relay power challenges
- Suitable for conventional or ICD decoder connections
- Includes easily activated solid state relay, and local 24V transformer for PSR activation
- Easy wiring with labeled wire connections
- NEMA 3R enclosure with standard key lock

ELECTRICAL SPECIFICATIONS

- Primary AC Power: 120/230 VAC, 50/60 Hz, 50W
- Output (to PSR): 25V, 1600 mA
- MV Input: Dual pole, double throw solid state relay (10 A)



PSRB Pump Start Relay Booster

Height: 8¾"
Width: 7"
Depth: 3¾"