PGP® ULTRA

Radius: 17' to 47' Flow: 0.36 to 14.8 GPM Inlet: 3/4"

ST SYSTEM

FEATURES

- Models: Shrub, 4", 12"
- Arc setting: 50° to 360°
- Factory installed rubber cover
- · Through-the-top arc adjustment
- QuickCheck™ arc mechanism
- · Water lubricated gear-drive
- Nozzle choices: 34
- Nozzle racks: 1.5 to 8.0 Blue, 2.0 to 4.5 Low Angle Gray, 0.50 to 3.0 Black, 6.0 to 13.0 Green, MPR-25, MPR-30, MPR-35
- Warranty period: 5 years
- ► Automatic arc return
- Non-strippable drive
- ▶ Part- and full-circle in one model
- Headed and slotted set screw
- ► Reclaimed water ID
- ▶ Drain check valve (up to 10' of elevation)

OPERATING SPECIFICATIONS

- Radius: 17' to 47'
- Flow: 0.36 to 14.8 GPM
- Recommended pressure range: 25 to 70 PSI
- Operating pressure range: 20 to 100 PSI
- Precipitation rates: 0.4 in/hr approximately
- Nozzle trajectory: Std = 25°, Low Angle = 13°
- Advanced Feature descriptions on page 30



PGP Ultra Reclaimed Available as a factory installed option on all models



PGP Ultra Easy arc and radius adjustment



PGP-00

Overall height: 71/2" Exposed diameter: 13/4" Inlet size: 3/4"



PGP-04

Overall height: 71/2" Pop-up height: 4" Exposed diameter: 13/4" Inlet size: 3/4"



PGP-12

Overall height: 17" Pop-up height: 12" Exposed diameter: 13/4" Inlet size: 3/4"

PGP-ULTRA - SI	PECIFICATION BUILDER:	ORDER 1	+ 2	2 +	3	+	4

1	Model	2	Standard Features	3	Feature Options	4	Nozzle Options
P	GP-00 = Shrub GP-04 = 4" Pop-up GP-12 = 12" Pop-up		ljustable arc, plastic riser, 8 standard zzles, and 4 low-angle nozzles	cv	ank) = No option = Drain check valve -R = Drain check valve and reclaimed water ID	Granding Gra	ue 1.5 - 8.0 ay Low Angle ack Short Radius een High Flow PR-25-Q, T, H, F PR-30-Q, T, H, F et o 4.0 = only nozzles - 4.0 can be factory-installed

Examples:

PGP-04 = 4" Pop-up, adjustable arc

PGP-04 - 2.5 = 4" Pop-up, adjustable arc, and 2.5 nozzle

 $\textbf{PGP-12-CV-R-4.0} = 12" \ \text{Pop-up, adjustable arc, with drain check valve and reclaimed water ID, and } 4.0 \ \text{nozzle}$