

PRO-C HYDRAWISE

Number of Stations: **4 - 16**
Type: **Modular**

FEATURES

- Wi-Fi-enabled for easy connection to the internet from any location
- Uses Hydrowise web-based software to offer automatic watering schedule updates
- Integrates local weather data to make water-saving schedule adjustments
- Utilizes Pro-C modules to create station counts between 4-16
- Built-in milliamp sensor
- Roam and Roam XL compatible
- Warranty: 2 years
- ▶ Touch-screen interface
- ▶ Predictive Watering™ adjustments
- ▶ Flow meter detection and alerts with optional HC Flow Meter
- ▶ Wiring detection and alerts
- ▶ Includes 5' lead and plug

ELECTRICAL SPECIFICATIONS

- Transformer input: 120 VAC
- P/MV: (24 VAC): 0.28 A
- Transformer output (24 VAC): 1 A
- Sensor inputs: 1
- Station output (24 VAC): 0.56 A
- Operating temperature: 0°F to 140°F

APPROVALS

- CE, UL, cUL, C-tick, FCC
- ▶ = *Advanced Feature descriptions on page 88*



Pro-C Hydrowise
Plastic Indoor/Outdoor
Height: 9"
Width: 10"
Depth: 4½"



HPC Face Panel

CONTROLLERS

PRO-C HYDRAWISE

Model	Description
HPC-400	4-station base: Domestic 110 VAC indoor/outdoor controller
HPC401E	4-station base: European 230 VAC indoor/outdoor controller
HPC401A	4-station base: Australian 230 VAC indoor/outdoor controller

PC-SERIES STATION EXPANSION

Modules	Description
PCM-300	3-station plug-in module: Use to increase station count from 4 to 7, 10, or 13
PCM-900	9-station plug-in module: Use to increase station count from 7 to 16

HPC FACE PANEL

Model	Description
HPC-FP	Hydrawise retrofit front panel for Pro-C controllers



PCM-300 and PCM-900 Expansion Modules
These modules are compatible with the new Pro-C 400 series.



EPA WaterSense Approved

Recognized as a responsible water-saving tool by the U.S. Environmental Protection Agency.