

G800 SERIES

Model: **G884**
 Radius: **14.9 to 29.6 m**
 Flow: **3.23 to 13.29 m³/hr; 53.8 to 221.4 l/min**

FEATURES

- Model: G884 - Full-circle
- Dual trajectory colour-coded nozzles:
 - 10 standard trajectory (22.5°)
 - 9 low-angle trajectory (15°)
- Nozzle range: #15 to #53
- Exclusive PressurePort™ nozzle technology
- Stainless steel riser
- Water-lubricated gear drive
- ▶ All TTS advanced features
- ▶ Decoder-In-Head (DIH) capable

OPERATING SPECIFICATIONS

- Radius: 14.9 to 29.6 m
- Flow: 3.23 to 13.29 m³/hr; 53.8 to 221.4 l/min
- Pressure range: 3.4 to 6.9 bar; 340 to 690 kPa
- All TTS rotors are pressure rated at 10 bar; 1000 kPa

OPTIONS

- C - Check-O-Matic checks up to 8 m in elevation change and readily converts to Normally-Open Hydraulic with through the top connections
- D - Decoder Valve-In-Head with all "E" specifications below*
- DD - Two-station Decoder Valve-In-Head with all "E" specifications below*
- E - Electric Valve-In-Head with adjustable pressure regulation, on-off-auto selector, 210 mA (370 mA inrush) 50Hz; 190 mA (350 mA inrush) 60Hz solenoid with captive plunger and internal downstream bleed

* All DIH rotors include two 3M DBRY-6 splices for connection to the two-wire path. See page 205 for critical recommendations on grounding DIH rotors.

▶ = TTS and DIH Advanced Features detailed on pages 174 and 176



G884C
 Pop-up height: 9.5 cm
 Overall height: 30 cm
 Flange diameter: 18 cm
 Female Inlet: 1½" ACME



G884E
 Pop-up height: 9.5 cm
 Overall height: 30 cm
 Flange diameter: 18 cm
 Female Inlet: 1½" ACME

G884 - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4 + 5

1 Model	2 Valve Options	3 Nozzle	4 Regulation*	5 Options
G884 = Full-Circle (convertible to forward-facing adjustable arc rotor)	C = Check-O-Matic* D = Decoder Valve-In-Head DD = Two-station Decoder Valve-In-Head E = Electric Valve-In-Head * Converts to N.O. Hydraulic Valve-In-Head	15 to 53 = Installed G880 Nozzle* * SSU = #18, #23, #25 or #48	P5 = 50 PSI (nozzles 15 to 18) P6 = 65 PSI (nozzles 18 to 25) P8 = 80 PSI (nozzles 25 to 35) * SSU = P5/#18, P6/#23 P8/#25, P8/#48	S = SSU* * Standard Stocking Unit

Example:
G884 - E - 48 - P8 - S = G884 full-circle electric valve-in-head, installed #48 nozzle, 80 PSI regulation, standard stocking unit model

GOLF ROTORS

G884 NOZZLE PERFORMANCE DATA*										
Nozzle Set			Pressure		Radius		Flow		Precip mm/hr	
			bar	kPa	m	m ³ /hr	l/min	■	▲	
● Tan 803611	○ 15 White	● Grey 315317	3.4	344	14.9	3.23	53.8	14.5	16.7	
			4.1	413	15.5	3.57	59.4	14.8	17.0	
			4.5	450	15.9	3.73	62.1	14.8	17.1	
			4.8	482	16.2	3.86	64.4	14.8	17.1	
● Tan 803611	○ 18 Orange	● Grey 315317	3.4	344	17.1	3.91	65.1	13.4	15.5	
			4.1	413	17.7	4.28	71.3	13.7	15.8	
			4.5	450	18.0	4.48	74.6	13.8	16.0	
			4.8	482	18.3	4.54	75.7	13.6	15.7	
● Tan 803611	○ 20 Brown	● Grey 315317	3.4	344	17.4	4.18	69.7	13.8	16.0	
			4.1	413	18.0	4.61	76.8	14.3	16.5	
			4.5	450	18.6	4.86	81.0	14.1	16.2	
			4.8	482	19.2	4.91	81.8	13.3	15.4	
● Tan 803611	○ 23 Green	● Lt. Blue 315311	3.4	344	19.2	4.91	81.8	13.3	15.4	
			4.1	413	19.8	5.22	87.1	13.3	15.4	
			4.5	450	20.1	5.45	90.8	13.5	15.6	
			4.8	482	20.4	5.66	94.3	13.6	15.7	
● Tan 803611	○ 25 Blue	● Lt. Blue 315311	4.5	450	21.6	6.50	108.3	13.9	16.0	
			4.8	482	22.3	6.75	112.5	13.6	15.7	
			5.5	551	22.6	7.19	119.8	14.1	16.3	
			6.2	620	22.9	7.65	127.5	14.6	16.9	
● Tan 803611	○ 33 Grey	● Lt. Blue 315311	4.5	450	22.6	7.02	117.0	13.8	15.9	
			4.8	482	22.9	7.27	121.1	13.9	16.1	
			5.5	551	23.5	7.77	129.5	14.1	16.3	
			6.2	620	24.1	8.22	137.0	14.2	16.4	
● Tan 803611	○ 38 Red	● Lt. Blue 315311	4.5	450	23.5	7.97	132.9	14.5	16.7	
			4.8	482	24.1	8.31	138.5	14.3	16.6	
			5.5	551	25.0	8.84	147.3	14.1	16.3	
			6.2	620	25.6	9.38	156.3	14.3	16.5	
● Tan 803611	○ 43 Dk. Brown	● Blue 315300	-	-	-	-	-	-	-	
			4.8	482	25.3	9.38	156.3	14.7	16.9	
			5.5	551	25.9	9.90	165.0	14.8	17.0	
			6.2	620	26.5	10.52	175.3	15.0	17.3	
● Dk. Brown 803610	○ 48 Dk. Green	● Dk. Blue 833500	-	-	-	-	-	-	-	
			4.8	482	27.4	10.65	177.5	14.2	16.3	
			5.5	551	28.0	11.11	185.1	14.1	16.3	
			6.2	620	28.7	11.46	191.0	14.0	16.1	
● Dk. Brown 803610	○ 53 Dk. Blue	● Dk. Blue 833500	-	-	-	-	-	-	-	
			4.8	482	27.7	11.31	188.5	14.7	17.0	
			5.5	551	28.3	11.86	197.7	14.8	17.0	
			6.2	620	29.0	12.61	210.1	15.0	17.4	
● Dk. Brown 803610	○ 53 Dk. Blue	● Dk. Blue 833500	6.9	689	29.6	13.29	221.4	15.2	17.6	

* Preliminary performance data. Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral. To calculate precipitation rates for 180° operation, multiply by 2.

G884 STANDARD NOZZLES

G884 LOW-ANGLE NOZZLES**



** Low-angle nozzles reduce radius by 15%



G885 Decoder-In-Head TTS Rotor

G885 TTS Rotor Spacious TTS Flange Compartment

All TTS rotors include ample room for solenoid splice connections and a decoder module when needed.