

G800 SERIES

Model: **G885**
 Radius: **11.3 to 28.7 m**
 Flow: **2.02 to 13.54 m³/hr; 33.7 to 225.6 l/min**

FEATURES

- Model: G885 - True full-circle/adjustable part-circle (60° to 360°)
- QuickCheck™ arc mechanism
- QuickSet-360 arc mechanism
- Dual trajectory colour-coded nozzles:
 - 12 standard trajectory (22.5°)
 - 9 low-angle trajectory (15°)
- Nozzle range: #10 to #53
- Exclusive PressurePort™ nozzle technology
- Contour “Back-Nozzle” capabilities
- Ratcheting stainless steel riser
- Water-lubricated gear drive
- ▶ All TTS advanced features
- ▶ Decoder-In-Head (DIH) capable

OPERATING SPECIFICATIONS

- Radius: 11.3 to 28.7 m
- Flow: 2.02 to 13.54 m³/hr; 33.7 to 225.6 l/min
- Pressure range: 3.4 to 6.9 bar; 340 to 690 kPa
- All TTS rotors are pressure rated at 10 bar; 1,000 kPa

OPTIONS

- C - Check-O-Matic checks up to 8 m in elevation change and readily converts to Normally-Open Hydraulic with through the top connections
- D - Decoder Valve-In-Head with all “E” specifications below*
- DD - Two-station Decoder Valve-In-Head with all “E” specifications below*
- E - Electric Valve-In-Head with adjustable pressure regulation, on-off-auto selector, 210 mA (370 mA inrush) 50Hz; 190 mA (350 mA inrush) 60Hz solenoid with captive plunger and internal downstream bleed

* All DIH rotors include two 3M DBRY-6 splices for connection to the two-wire path. See page 205 for critical recommendations on grounding DIH rotors.

▶ = TTS and DIH Advanced Features detailed on pages 174 and 176



G885C

Pop-up height: 9.5 cm
 Overall height: 30 cm
 Flange diameter: 18 cm
 Female Inlet: 1½" ACME



G885E

Pop-up height: 9.5 cm
 Overall height: 30 cm
 Flange diameter: 18 cm
 Female Inlet: 1½" ACME

G885 - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4 + 5

1 Model	2 Valve Options	3 Nozzle	4 Regulation*	5 Options
G885 = Full/Part-Circle 60°-360° Arc Range	C = Check-O-Matic* D = Decoder Valve-In-Head DD = Two-station Decoder Valve-In-Head E = Electric Valve-In-Head * Converts to N.O. Hydraulic Valve-In-Head	10 to 53 = Installed G885 Nozzle* * SSU = #18, #23, #25 or #48	P5 = 50 PSI (nozzles 10 to 18) P6 = 65 PSI (nozzles 18 to 25) P8 = 80 PSI (nozzles 25 to 53) * SSU = P5/#18, P6/#23 P8/#25, P8/#48	S = SSU* * Standard Stocking Unit

Example:

G885 - E - 48 - P8 - S = G885 full/part circle electric valve-in-head, installed #48 nozzle, 80 PSI regulation, standard stocking unit model

GOLF ROTORS

G885 NOZZLE PERFORMANCE DATA*

Nozzle Set			Pressure		Radius	Flow		Precip mm/hr	
			bar	kPa	m	m ³ /hr	l/min	■	▲
Orange	10	Dk. Green	3.4	344	11.3	2.02	33.7	15.9	18.4
●		●	4.1	413	11.9	2.23	37.1	15.8	18.2
803603		315312	4.5	450	12.5	2.32	38.6	14.8	17.1
		Lt. Green	-	-	-	-	-	-	-
Orange	13	White	3.4	344	14.3	2.59	43.2	12.6	14.6
●		●	4.1	413	14.6	2.79	46.6	13.1	15.1
803603		315314	4.5	450	14.9	2.93	48.8	13.1	15.2
		Lt. Blue	-	-	-	-	-	-	-
Orange	15	White	3.4	344	15.9	2.93	48.8	11.7	13.5
●		●	4.1	413	15.9	3.29	54.9	13.1	15.1
803603		315314	4.5	450	16.2	3.38	56.4	13.0	15.0
		White	4.8	482	16.2	3.52	58.7	13.5	15.6
Orange	18	Lt. Green	3.4	344	17.4	3.77	62.8	12.5	14.4
●		●	4.1	413	17.7	4.04	67.4	12.9	14.9
803603		315313	4.5	450	18.0	4.23	70.4	13.1	15.1
		Orange	4.8	482	18.3	4.41	73.4	13.2	15.2
Orange	20	Lt. Green	3.4	344	18.0	4.07	67.8	12.6	14.5
●		●	4.1	413	18.6	4.43	73.8	12.8	14.8
803603		315313	4.5	450	18.9	4.50	75.0	12.6	14.5
		Tan	4.8	482	19.2	4.68	78.0	12.7	14.7
Orange	23	Lt. Green	3.4	344	19.8	4.59	76.5	11.7	13.5
●		●	4.1	413	20.1	5.02	83.7	12.4	14.3
803603		315313	4.5	450	20.4	5.43	90.5	13.0	15.0
		Green	4.8	482	20.4	5.50	91.6	13.2	15.2
Red	25	Green	4.5	450	21.6	6.43	107.1	13.7	15.8
●		●	4.8	482	21.9	6.66	110.9	13.8	16.0
803602		315310	5.5	551	22.3	7.16	119.2	14.5	16.7
		Blue	6.2	620	22.6	7.59	126.4	14.9	17.2
Red	33	Green	4.5	450	21.9	6.95	115.8	14.4	16.7
●		●	4.8	482	22.3	7.18	119.6	14.5	16.7
803602		315310	5.5	551	22.9	7.70	128.3	14.7	17.0
		Grey	6.2	620	23.5	8.13	135.5	14.8	17.0
Red	38	Green	4.5	450	23.2	7.93	132.1	14.8	17.1
●		●	4.8	482	23.8	8.22	137.0	14.5	16.8
803602		315310	5.5	551	24.4	8.88	148.0	14.9	17.2
		Red	6.2	620	25.0	9.36	156.0	15.0	17.3
Red	43	Green	4.8	482	24.7	9.36	156.0	15.4	17.7
●		●	5.5	551	25.3	9.88	164.7	15.4	17.8
803602		315310	6.2	620	26.2	10.49	174.9	15.3	17.6
		Dk. Brown	6.9	689	27.1	11.06	184.3	15.0	17.4
Dk. Red	48	Dk. Green	4.8	482	25.3	10.52	175.3	16.4	19.0
●		●	5.5	551	25.9	10.99	183.2	16.4	18.9
803601		315312	6.2	620	27.1	11.74	195.7	16.0	18.4
		Dk. Green	6.9	689	27.7	12.38	206.3	16.1	18.6
Dk. Red	53	Dk. Green	4.8	482	26.5	11.52	191.9	16.4	18.9
●		●	5.5	551	27.1	12.06	201.0	16.4	18.9
803601		315312	6.2	620	28.0	12.81	213.5	16.3	18.8
		Dk. Blue	6.9	689	28.7	13.54	225.6	16.5	19.0

● = Nozzle plug P/N 315300 installed in the back side of the nozzle housing.

* Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral. To calculate precipitation rates for 180° operation, multiply by 2.

G885 STANDARD NOZZLES

G885 LOW-ANGLE NOZZLES**



** Low-angle nozzles reduce radius by 15%



Contour "Back-Nozzle" Capabilities

Whether you want a little extra green behind your adjustable arc G885 rotors or a more "modeled" look to your fairway's hard edges, Contour "Back-Nozzles" are here to make your vision a reality. Choose from four short-range or four mid-range nozzles to suit your needs.

CONTOUR BACK-NOZZLE PERFORMANCE DATA

P/N	Colour	Profile	4.5 Bar		5.5 Bar	
			Metres	L/M	Metres	L/M
803604	Peach		7.6	12.9	8.2	14.8
803603	Orange		8.5	14.4	8.8	15.9
803602	Red		9.4	15.9	10.1	17.0
803601	Dk. Red		10.4	17.4	11.0	18.5
315314	White		11.3	10.6	11.6	11.0
315313	Lt. Green		12.8	16.3	13.4	17.8
315310	Green		14.0	19.7	14.6	21.6
315312	Dk. Green		14.9	29.9	15.5	33.3

G885 CONTOUR BACK-NOZZLES



QuickSet-360 with Ratcheting Riser

Setting up your adjustable arc G885 is fast and simple. The integrated ratcheting mechanism allows a simple twist of the riser to align the right-side reversing point. The G885 is also easily convertible to a true non-reversing full-circle rotor with our exclusive QuickSet-360 feature.