

## **690 – COLOR FAST (LIQUID ADDITIVE)**

*Color Fast* liquid additive is designed to incorporate color into the Texture-Krete 2000 Deck System. When blended with ICT Liquid Resin, *Color Fast* additive allows the user to create most ICT colors for use as bases (grout lines) and colored texture or hand troweled finishes.

### **FEATURES & BENEFITS:**

#### **Features:**

- Pre-measured bottle
- Simple 3-step preparation
- Compact 12oz. size

#### **Benefits:**

- Color consistency throughout
- Easy to use and apply
- Easy to store and ship, no more 5gal pails

### **CHARACTERISTICS:**

- Appearance: Liquid based, color will vary
- Clean-up: Soap and Water

### **LIMITATIONS:**

*Color Fast* liquid additive **must** be added when ICT Liquid Resin is in the “**Ready-to-Use**” state. One bottle of *Color Fast* liquid additive will color one five gallon pail of Liquid Resin. *Color Fast* liquid additive **should not** be added to ICT Concentrated Resin unless resin is cut first. Color will not match if this is done.

### **INSTRUCTIONS FOR USE:**

Shake container of colorant 1-2 minutes. Dispense entire bottle into “Ready-to-use” Liquid Resin five gallon pail. Fill *Color Fast* container half full with clean water and shake again. Pour remainder into same Liquid Resin pail. **Make sure no colorant is left in bottle.** Mix or “Box” entire five gallon pail thoroughly to ensure color uniformity. **Note:** When two or more pails are to be colored with same color for one job, prepare all colorant first and mix or “Box” all batches before using to ensure color uniformity. Repeat mixing or “Boxing” step several times during job to ensure color uniformity.

### **PACKAGING:**

- 12oz. Bottles (all colors except below)
- 40oz. Bottles (Terracotta, Mocca, Black)

## 690 – COLOR FAST (LIQUID ADDITIVE) (CONT.)

### **PRECAUTIONS:**

- Keep from freezing
- Avoid contact with Skin and Eyes
- Do not store in direct sunlight
- Do not breath vapors
- Do not take internally
- **Keep Out Of Reach Of Children**

All Innovative Concrete Technology Corp. products are manufactured with the finest raw materials. Shelf life is 12 months from date of purchase when maintained in protected storage of 50F to 90F. It is the applicator's responsibility to determine the appropriate use of the product. All recommendations and suggestions are made without warranty, express or implied, since conditions of use are beyond our control. ICT Corp. disclaims any liability incurred in connection with the use of these data or suggestions.