

# MATERIAL SAFETY DATA SHEET

## Innovative Concrete Technology Corp.

2410 McJunkin Rd.  
Lakeland, FL 33801

Emergency Telephone: 888-296-5236

## Section 1 - Product Information

**Product name:** Color Fast (tint additive)

**Description:** Color additive for ICT Liquid Resin

**Synonyms:** None

**Molecular Formula:** N/A

**Chemical Family:** N/A

## Section 2 - Hazardous Ingredients

Chemical Names(s):	CAS Number	OSHA PEL
P -Series Ethers	29911-28-2	not established
	132739-31-2	not established
	4590-94-8	not established

## Section 3 - Physical Properties

Color: Pigmented and Clear

Appearance:

Odor: Mild amine

Evaporation Rate: Slower than ether

Specific Gravity: 1.3

PH:9.0

Boiling Point: > 212F

Solubility in water: Partially Miscible

## Section 4 - Fire and Explosion Data

**Flash Point:**

**Extinguishing Media:** Use water fog, foam, CO2 or dry chemical extinguishing media.

**Fire Fighting Procedures:** Firefighters should be equipped with self-contained breathing apparatus and turn out gear.

**Unusual Hazards:** There are no known unusual fire or explosion hazards.

## Section 5 - Health Effects

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

**Acute Overexposure Effects:**

Based on test data and experience with similar products it is believed that this is a low hazard material. Ingestion may cause gastric upset, pain, diarrhea, lethargy. Inhalation of the vapors may result in respiratory irritation.

**Chronic Overexposure Effects:**

There are no known chronic effects associated with this material.

**First Aid Procedures:**

**Skin:** Wash affected areas with soap and water. Remove and launder contaminated clothing before reuse. If irritation develops, get medical attention.

**Eyes:** Immediately rinse eyes with running water for 15 minutes. If irritation develops, get medical attention.

**Ingestion:** If swallowed, dilute with water and immediately induce vomiting. Never give fluids or induce vomiting if the victim is unconscious or having convulsions. Get immediate medical attention.

---

## Section 6 - Reactivity Data

---

**Stability Data:** Stable

**Incompatibility:** Metal salt could coagulate the product.

**Condition /Hazards to Avoid:** Maintain storage temperature at 50-90F. Keep From Freezing.

**Hazardous Polymerization:** Does not occur.

**Corrosive Properties:** Not corrosive

**Oxidizer Properties:** Not an oxidizer.

---

## Section 7 - Personal Protection

---

**Clothing:** Gloves, coveralls, apron, and boots as necessary to prevent contact.

**Eyes:** Chemical goggles; also wear a face shield if splashing hazard exists.

**Respiration:** If vapors or mists are generated, wear a NIOSH /MSHA approved if allergies to said product exist.

**Ventilation:** Open all doors windows to allow for adequate air flow and circulation.

---

## Section 8 - Spill and leak / environmental

---

Spills should be contained and placed in suitable containers for disposal in a licensed facility. This material is not regulated by RCRA or CERCLA.

**Waste Disposal:** Incinerate or bury as a solid in a licensed facility. Do not discharge into waterways or sewer systems without proper authority.

**Container Disposal:** Recommended crushing or other means to prevent unauthorized reuse

## Section 9 - Regulatory Information

---

RCRA Hazardous Waste Number: N/A

CERCLA: No

**HAZARD RATING:**    **Health- 1**                      **Fire- 1**                      **Reactivity- 0**                      **Special: NA**

This product is not a physical hazard of a health according to the OSHA Hazard Communication Standards.

The information contained herein is to our knowledge true and accurate. All recommendations and suggestions are made without guarantee, since the condition of use are beyond our control.