

Total Wash

Sprayer & Equipment Cleaner

760

USE:

ICT Total Wash (760) is a specialty cleaner used to remove residue left behind by *Ure-Seal H₂O (150/151/152/154)* from sprayers, brushes, roller covers, and other equipment.

DESCRIPTION:

Total Wash (760) is a concentrated, water-reducible solvent. It is safe to use on most commonly used pieces of equipment that may be used in the application of *Ure-Seal H₂O (150/151/152/154)*.

FEATURES & BENEFITS:

- Easily removes wet/damp *Ure-Seal H₂O* residue
- Safe to use on most common tools and sprayers
- Can be filtered and re-used until *Total Wash (760)* is no longer clear

INSTRUCTIONS FOR USE:

When using *Total Wash (760)* to clean brushes, rollers covers, and other small pieces of equipment, soak items in *Total Wash (760)* until residue is able to be rinsed or wiped clean, no longer than 10-15 minutes. When cleaning a sprayer, first flush with warm water and sodium bicarbonate (baking soda). Then run *Total Wash (760)* through entire machine continuously for 3-5 minutes. Be sure to flush sprayer thoroughly afterwards with water to ensure that cross contamination does not occur. *Total Wash (760)* can be diluted, but should not exceed, 1:1 with water.

Note: Sprayers must have Viton O-rings to be able to use Total Wash (760). Total Wash (760) must be used immediately after completion of job. Do not allow Ure-Seal H₂O to dry. Total Wash (760) will not remove dried Ure-Seal H₂O.

PRECAUTIONS:

Do not discharge into drains or the environment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport, or handle hazardous waste shall take necessary measures to prevent risks of pollution or damage to people or animals. Recycle by distillation. Remove to an authorized waste incinerator for solvents with energy recovery. May be discharged to wastewater treatment installation.

May be harmful if swallowed.

Do not inhale. Use in well ventilated area.

Avoid contact with skin, eyes, and clothing.

Wear gloves, eye protection, and protective clothing when handling. Use full face mask with filter type A whenever necessary.

Keep Out Of Reach Of Children

CHARACTERISTICS AND TECHNICAL DATA	
Color	No color
Odor	Mild odor
Flash Point	68—70 °C

ICT Corporation

2410 McJunkin Road * Lakeland, FL 33803

(Nationwide): 888-296-5236 * (Local): 863-665-8787 * (Fax): 863-666-2768

(Email): info@innovativeconcrete.com

www.innovativeconcrete.com

All Innovative Concrete Technology Corp. products are manufactured with the finest raw materials. Shelf life is 2 years from the date of manufacturing when maintained in protected storage of 50°F to 90°F. It is the applicator's responsibility to determine the appropriate use of the product. All recommendations and suggestions are made without warranty, express or implied, since conditions of use are beyond ICT's control. ICT Corp. disclaims any liability incurred in connection with the use of these data or suggestions.