

# Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

4 Identification
1 Identification
<sup>·</sup> Product identifier <sup>·</sup> Trade name: <u>150 URE-SEAL H2O Gloss Part B</u>
151 URE-SEAL H2O Natural Part B 152 URE-SEAL H2O Mid Gloss Part B 153 URE-SEAL H2O 7:1 PART B
· Other means of identification: No other identifiers
<ul> <li>Recommended use and restriction on use</li> <li>Recommended use: Polyurethane resin</li> <li>Restrictions on use: No relevant information available.</li> </ul>
· Details of the supplier of the Safety Data Sheet
<ul> <li>Manufacturer/Supplier: Innovative Concrete Technology Corp.</li> <li>2410 McJunkin Road Lakeland, FL 33803</li> </ul>
(863) 665-8787 sales@innovativeconcrete.com
<ul> <li>Emergency telephone number: ChemTel Inc.</li> <li>800-255-3924 (North America)</li> <li>(813)248-0585 (International)</li> </ul>
2 Hazard(s) identification
<ul> <li>Classification of the substance or mixture</li> <li>Acute Tox. 4 H332 Harmful if inhaled.</li> <li>Skin Sens. 1 H317 May cause an allergic skin reaction.</li> <li>STOT SE 3 H335 May cause respiratory irritation.</li> </ul>
· Label elements · GHS label elements
The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms:
GHS07
· Signal word: Warning · Hazard statements:
H332 Harmful if inhaled. H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation. • Precautionary statements:
<ul><li>P261 Avoid breathing dust/fume/gas/mist/vapors/spray</li><li>P271 Use only outdoors or in a well-ventilated area.</li></ul>
P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves.
P302+P352 If on skin: Wash with plenty of soap and water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. (Cont'd. on page 2)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

#### Trade name: 150 URE-SEAL H2O Gloss Part B 151 URE-SEAL H2O Natural Part B 152 URE-SEAL H2O Mid Gloss Part B

(Cont'd. of page 1)

P312 Call a poison center/doctor if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• Other hazards There are no other hazards not otherwise classified that have been identified.

## 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

#### · Components:

· Components:	
28182-81-2 Hexamethylene diisocyanate, homopolymer	60-80%
Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	
666723-27-9 Hydrophilic aliphatic polyisocyanate based on hexamethylene diisod	cyanate 10-30%
Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	
98-94-2 cyclohexyldimethylamine	0.1-1%
<ul> <li>Flam. Liq. 3, H226</li> <li>Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331</li> <li>Skin Corr. 1B, H314; Eye Dam. 1, H318</li> </ul>	
822-06-0 hexamethylene-di-isocyanate	<0.5%
Acute Tox. 3, H311; Acute Tox. 1, H330 Resp. Sens. 1, H334	
Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin H317; STOT SE 3, H335	Sens. 1,
· Additional information:	

#### Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

This product contains an amine neutralizing agent which is bound in the matrix of this product as a salt. This amine salt is considered essentially unreactive at room temperature. Generation of amine vapors is expected when this product is processed (heated) during the drying/hardening of the coating.

### 4 First-aid measures

#### <sup>•</sup> Description of first aid measures

#### • After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

#### • After skin contact:

Immediately remove any clothing soiled by the product. Immediately wash with water and soap and rinse thoroughly. If skin irritation or rash occurs: Get medical advice/attention.

#### · After eye contact:

Immediately remove contact lenses if possible.

(Cont'd. on page 3)



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

## Trade name: 150 URE-SEAL H2O Gloss Part B 151 URE-SEAL H2O Natural Part B

152 URE-SEAL H2O Mid Gloss Part B

(Cont'd, of page 2)

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Breathing difficulty

Coughing

Allergic reactions

May cause respiratory irritation.

Danger: Harmful if inhaled.

Indication of any immediate medical attention and special treatment needed:

Medical supervision for at least 48 hours.

Treat symptomatically.

#### 5 Fire-fighting measures

#### • Extinguishing media

• Suitable extinguishing agents:

- CO2, extinguishing powder or water spray. Fight larger fires with water spray.
- For safety reasons unsuitable extinguishing agents: Water stream.
- Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

• Advice for firefighters

#### · Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

#### 6 Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation.

Use respiratory protective device against the effects of fumes/dust/aerosol.

#### **Environmental precautions**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

#### Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

## Ensure adequate ventilation.

Send for recovery or disposal in suitable receptacles.

#### **Reference to other sections**

See Section 7 for information on safe handling.

- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

Trade name: 150 URE-SEAL H2O Gloss Part B 151 URE-SEAL H2O Natural Part B 152 URE-SEAL H2O Mid Gloss Part B

(Cont'd. of page 3)

## 7 Handling and storage

#### Handling

#### · Precautions for safe handling:

Use only in well ventilated areas.

Avoid breathing dust.

Avoid breathing mist, vapors, or spray.

Avoid contact with the eyes and skin.

Open and handle receptacle with care.

#### • Conditions for safe storage, including any incompatibilities Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles. Store in a well-ventilated place. Keep cool. Store at 41-95 °F / 5-30 °C.

· Information about storage in one common storage facility: Store away from foodstuffs.

Store away from water.

Specific end use(s) No relevant information available.

8 Exposure co	ontrols/personal protection	
· Control para		
	vith limit values that require monitoring at the workplace:	
98-94-2 cycloh	exyldimethylamine	
EV (Canada)	Short-term value: 26 mg/m <sup>3</sup> , 5 ppm	
822-06-0 hexar	nethylene-di-isocyanate	
REL (USA)	Long-term value: 0.035 mg/m <sup>3</sup> , 0.005 ppm Ceiling limit value: 0.14* mg/m <sup>3</sup> , 0.02* ppm *10-min	
TLV (USA)	Long-term value: 0.034 mg/m³, 0.005 ppm BEI	
EL (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm S(R)	
EV (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.02 ppm	
LMPE (Mexico)	Long-term value: 0.005 ppm	
The usual preca Keep away fron Immediately rer Wash hands be	ntrols Ective and hygienic measures: autionary measures for handling chemicals should be followed. In foodstuffs, beverages and feed. move all soiled and contaminated clothing. efore breaks and at the end of work. dust/fume/gas/mist/vapors/spray.	(Cont'd. on page 5)



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

#### Trade name: 150 URE-SEAL H2O Gloss Part B 151 URE-SEAL H2O Natural Part B 152 URE-SEAL H2O Mid Gloss Part B

(Cont'd. of page 4)

Avoid contact with the eyes and skin.

• Engineering controls: Provide adequate ventilation.

- Breathing equipment: Suitable respiratory protective device recommended.
- Protection of hands:



Protective gloves

## · Material of gloves

Butyl rubber, BR Nitrile rubber, NBR Neoprene gloves **Eye protection:** 



Safety glasses

· Body protection: Protective work clothing

· Limitation and supervision of exposure into the environment

No relevant information available.

• Risk management measures No relevant information available.

Information on basic physical a	and chemical properties	
Appearance:		
Form:	Liquid	
Color:	Light yellow	
Odor:	Slight	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	Not determined.	
Flash point:	185 °C (365 °F)	
Flammability (solid, gaseous):	Not applicable.	
Auto-ignition temperature:	445 °C (833 °F)	
Decomposition temperature:	181 °C (357.8 °F)	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
Oxidizing properties:	Not determined.	



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Page: 6/10

Revision: December 11, 2019

#### Trade name: 150 URE-SEAL H2O Gloss Part B 151 URE-SEAL H2O Natural Part B 152 URE-SEAL H2O Mid Gloss Part B

		(Cont'd. of page 5
· Vapor pressure:	Not determined.	
· Density:		
Relative density:	1.15	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/w	ater): Not determined.	
· Viscosity		
Dynamic at 20 °C (68 °F):	800 mPas	
Kinematic:	Not determined.	
<sup>·</sup> Other information	No relevant information available.	

#### 10 Stability and reactivity

· Reactivity: No relevant information available.

· Chemical stability: Stable under normal temperatures and pressures.

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

<sup>•</sup> Possibility of hazardous reactions

Reacts with light alloys. Reacts with strong alkali.

Reacts with amines.

Reacts with alcohols.

Conditions to avoid

Excessive heat.

Do not allow product to freeze.

<sup>•</sup> Incompatible materials

Alkalis.

Alcohols

Amines Water

Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

Nitrogen oxides

Isocyanate Hydrogen cyanide (prussic acid)

11 Toxicological information

<sup>·</sup> Information on toxicological effects

(Cont'd. on page 7)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

#### Trade name: 150 URE-SEAL H2O Gloss Part B 151 URE-SEAL H2O Natural Part B 152 URE-SEAL H2O Mid Gloss Part B

(Cont'd. of page 6) · Acute toxicity: Harmful if inhaled. · LD/LC50 values that are relevant for classification: 28182-81-2 Hexamethylene diisocyanate, homopolymer Oral LD50 >5000 mg/kg (rat) Dermal LD50 >5000 mg/kg (rabbit) 98-94-2 cyclohexyldimethylamine LD50 Oral 272 mg/kg (rat) Dermal LD50 >400 mg/kg (rat) Inhalative LC50/4h 4.45 mg/l (rat) 822-06-0 hexamethylene-di-isocyanate Oral LD50 959 mg/kg (rat) Dermal LD50 593 mg/kg (rat) Inhalative LC50/4h 124 mg/l (rat) Primary irritant effect: · On the skin: Based on available data, the classification criteria are not met. • On the eve: Based on available data, the classification criteria are not met. · Sensitization: Sensitization possible through skin contact. · IARC (International Agency for Research on Cancer): None of the ingredients are listed. • NTP (National Toxicology Program): None of the ingredients are listed. OSHA-Ca (Occupational Safety & Health Administration): None of the ingredients are listed. · Probable route(s) of exposure: Ingestion. Inhalation. Eve contact. Skin contact. · Germ cell mutagenicity: Based on available data, the classification criteria are not met. · Carcinogenicity: Based on available data, the classification criteria are not met. • **Reproductive toxicity:** Based on available data, the classification criteria are not met. • **STOT-single exposure:** May cause respiratory irritation. • STOT-repeated exposure: Based on available data, the classification criteria are not met. · Aspiration hazard: Based on available data, the classification criteria are not met. 12 Ecological information

<sup>·</sup> Toxicity

• Aquatic toxicity Harmful to aquatic life with long lasting effects.

- · Persistence and degradability Not easily biodegradable
- · Bioaccumulative potential: Non significant accumulation in organisms

• **Mobility in soil:** No relevant information available.

(Cont'd. on page 8)



(Cont'd. of page 7)



## Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

#### Trade name: 150 URE-SEAL H2O Gloss Part B 151 URE-SEAL H2O Natural Part B 152 URE-SEAL H2O Mid Gloss Part B

• Other adverse effects No relevant information available.

## 13 Disposal considerations

#### <sup>·</sup> Waste treatment methods

#### · Recommendation:

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

#### <sup>·</sup> Uncleaned packagings

• Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
UN proper shipping name		
DOT	Not regulated.	
ADR/RID/ADN, IMDG, IATA	Not regulated.	
Transport hazard class(es)		
DOT, ADR/RID/ADN, IMDG, IATA		
Class	Not regulated.	
Packing group		
DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
Environmental hazards		
Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	c II of	
MARPOL73/78 and the IBC Code	Not applicable.	

### **15 Regulatory information**

 Safety, health and environmental regulations/legislation specific for the substance or mixture
 United States (USA)

· SARA

#### Section 302 (extremely hazardous substances):

None of the ingredients are listed.

(Cont'd. on page 9)



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

#### Trade name: 150 URE-SEAL H2O Gloss Part B 151 URE-SEAL H2O Natural Part B 152 URE-SEAL H2O Mid Gloss Part B

(Cont'd. of page 8)

#### • Section 355 (extremely hazardous substances):

None of the ingredients are listed.

#### • Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

#### · TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

#### · Proposition 65 (California)

· Chemicals known to cause cancer:

None of the ingredients are listed.

#### · Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

Canadian Domestic Substances List (DSL):

All ingredients are listed or exempt.

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### • Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent OSHA: Occupational Safety & Health Administration Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 3: Acute toxicity - Category 3 Acute Tox. 1: Acute toxicity - Category 1 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: December 11, 2019

#### Trade name: 150 URE-SEAL H2O Gloss Part B 151 URE-SEAL H2O Natural Part B 152 URE-SEAL H2O Mid Gloss Part B

(Cont'd. of page 9)

Sources
Website, European Chemicals Agency (echa.europa.eu)
Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do)
Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.
Safety Data Sheets, Individual Manufacturers
SDS Prepared by:
ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com