

LED Pool and Spa Lights

Underwater LED lights for pools and spas. WaterColors offer energy efficiency in an ultra-slim profile and simple installation. WaterColors are ETL® classified to fit into some existing pool and spa niches as well as ProNiches.

Features:

- Stainless steel housing for corrosion-free performance
- Choose from nine vibrant colors or five dramatic light shows
- Microprocessor blended colors for smooth transitions and no moving parts
- Long life, less than 50 watts of power, available in 120V & 12V versions
- Controlled by a single light switch or seamlessly interfaces with our Smart Color Control
- ETL Listed to be installed in ProNiche or other manufacturers' niches



WaterColors Pool and Spa LED Color Lights

Part No.	Description	Face Ring	Voltage	Wattage	Cable Length
Large LED Lights: Dimensions, 3.24" Depth x 10.04" Diameter					
CPHVRGBWS30	Large LED Light, 120V, 30'	SS	120V	50W	30 ft.
CPHVRGBWS50	Large LED Light, 120V, 50'	SS	120V	50W	50 ft.
CPHVRGBWS100	Large LED Light, 120V, 100'	SS	120V	50W	100 ft.
CPHVRGBWP100	Large LED Light, 120V, 100'	Plastic	120V	50W	100 ft.
CPHVRGBWS150	Large LED Light, 120V, 150'	SS	120V	50W	150 ft.
CPHVRGBWS250	Large LED Light, 120V, 250'	SS	120V	50W	250 ft.
CPLVRGBWS30	Large LED Light, 12V, 30'	SS	12V	50W	30 ft.
CPLVRGBWS50	Large LED Light, 12V, 50'	SS	12V	50W	50 ft.
CPLVRGBWS100	Large LED Light, 12V, 100'	SS	12V	50W	100 ft.
CPLVRGBWP100	Large LED Light, 12V, 100'	Plastic	12V	50W	100 ft.
CPLVRGBWS150	Large LED Light, 12V, 150'	SS	12V	50W	150 ft.
Small LED Lights: Dimensions, 120V 3.23" Depth x 5.81" Diameter; 12V 1.54" Depth x 5.81" Diameter					
CSHVRGBWS30	Small LED Light, 120V, 30'	SS	120V	25W	30 ft.
CSHVRGBWS50	Small LED Light, 120V, 50'	SS	120V	25W	50 ft.
CSHVRGBWS100	Small LED Light, 120V, 100'	SS	120V	25W	100 ft.
CSHVRGBWP100	Small LED Light, 120V, 100'	Plastic	120V	25W	100 ft.
CSHVRGBWS150	Small LED Light, 120V, 150'	SS	120V	25W	150 ft.
CSHVRGBWS250	Small LED Light, 120V, 250'	SS	120V	25W	250 ft.
CSLVRGBWS30	Small LED Light, 12V, 30'	SS	12V	25W	30 ft.
CSLVRGBWS50	Small LED Light, 12V, 50'	SS	12V	25W	50 ft.
CSLVRGBWS100	Small LED Light, 12V, 100'	SS	12V	25W	100 ft.
CSLVRGBWS150	Small LED Light, 12V, 150'	SS	12V	25W	150 ft.

See chart on next page for ETL listed wet niche fixtures.

Notes:

1. All 120V pool and spa lights must be connected to a branch circuit protected by a ground circuit (GFCI).
2. A separate 12VAC transformer is required on all 12V models. Transformer must be listed or certified by a Nationally Recognized Testing Lab (NRTL) (e.g., UL®, ETL, CSA®) for the application.
3. If installing 12V lights it is not recommended to use cord lengths greater than 50'. **A significant voltage drop will occur that dramatically reduces the light output.** Refer to the installation manual for wire voltage losses and potential effect.
4. When ordering, allow 4' of extra cable to coil inside light niche for serviceability.
5. Requires REV 0.2 or later for AquaLink® RS to operate light shows. REV 4.0 or later for PDA.