



NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: 196263 CUST PN: B2748 HP: 2.0 SF: 1.3 ROT: CCWPE RPM: 3450 TYPE: CX CODE: G FORM: KJM FRAME: Y 56 Y VOLTS: 230 AMPS: - MAX AMPS: - SF AMPS: 11.5 PH: 1 HZ: 60 INS: F AMB: 50 °C DUTY: CONT ENCLOSURE: ODP THERMALLY PROTECTED	<p>USE COPPER CONDUCTORS ONLY. INSTALL MOTOR WITH VENTS DOWN. ACCEPTABLE FOR FIELD WIRING</p>	<ol style="list-style-type: none"> FOR THREADED SHAFT EXTENSION ECCENTRICITY OF THREADED PORTION OF SHAFT IS HELD WITHIN .004[.10] TOTAL GAGE READING WITH THE INDICATOR ON O.D. OF GROUND RING GAGE AS SHOWN. THE GAGE BEING STATIONARY WITH RESPECT TO THE ROTOR. END PLAY NOT TO EXCEED .010[.25] MEASURED WITH NO THRUST. FINISH PAINT TO BE BLACK. REFERENCE MODEL: B748

PERFORMANCE CURVE	APPROVED SAMPLE		
15593311	0601158		
UL COMPONENT	CSA		
FILE#	CCN#	FILE#	GUIDE#
PENDING	PENDING	PENDING	PENDING
CUSTOMER	DSITRIBUTION		

DRAWING REVISION	REVISION BY	DATE	TOLERANCES UNLESS OTHERWISE SPECIFIED
F	J.AGUILERA	02-11-2015	DEC. INCH mm ANGLE
ECO	D.VALENCIANO	02-11-2015	.XX ±0.02 [±0.51] ±0.5°
ECO DESCRIPTION			.XXX ±0.005 [±0.127]
SEE ECO			.XXXX ±0.0005 [±0.0127]
			REMOVE BURRS & BREAK SHARP EDGES .003/015 [0.076/3.81]
			CORNER FILLETS .02 [1.51]
			MACHINED SURFACES $\sqrt{125}$ INCH $\sqrt{3.2}$ mm
			mm SHOWN IN [BRACKETS]

DRAWN BY:	DATE:	APPROVED BY:	DATE:	REFERENCE:	MATERIAL:	PROCESS/FINISH:
BL	09-01-2009	SH	09-01-2009			
REGAL™ Regal Beloit America, Inc.			MODEL-CFHP-56FR OUTLINE			
THIRD ANGLE PROJECTION			SIZE DWG NO C B2748		SHEET 1	