



NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: 164300 CUST PN: B123 HP: 1.5 SF: 1.30 ROT: CCWPE RPM: 3450 TYPE: CX CODE: H FORM: - FRAME: P 56 C VOLTS: 230/115 AMPS: SF 9.2/18.4 MAX AMPS: - SF AMPS: - PH: 1 HZ: 60 INS: B AMB: 50°C DUTY: CONT ENCLOSURE: ODP THERMALLY PROTECTED	<p>LOW VOLTAGE: BROWN → B, WHITE → L1, WHITE → L2, *A</p> <p>HIGH VOLTAGE: WHITE → B, L1 → L1, L2 → L2, BROWN → A</p> <p>NON-REVERSIBLE</p>	<ol style="list-style-type: none"> PILOT DIAMETER IS CONCENTRIC WITH SHAFT CENTERLINE WITHIN .004[.10] T.I.R. FACE OF MOUNTING FLANGE IS PERPENDICULAR TO SHAFT CENTERLINE WITHIN .004[.10] T.I.R. SHAFT RUNOUT NOT TO EXCEED .002[.05] T.I.R END PLAY NOT TO EXCEED .010[.25] MEASURED WITH NO THRUST FINISH PAINT TO BE BLACK

PERFORMANCE CURVE	APPROVED SAMPLE
16345311	-
UL COMPONENT	CSA
FILE# CCN# FILE# GUIDE#	
E14663 XZWR2 LR4642 4211-01	
CUSTOMER	DISTRIBUTION

DRAWING REVISION: D	REVISION BY: JAGUILERA	DATE: 01-23-2015	TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY: KHR	Regal Beloit America, Inc.
ECO: 0066358	APPROVED BY: D.VALENCIANO	DATE: 01-23-2015	DEC. INCH mm ANGLE	DATE: 08-30-2005	
ECO DESCRIPTION: SEE ECO			.X ±0.1 [±2.5] ±0.5°	APPROVED BY: JMW	DESCRIPTION: MODEL-CFHP-56FR OUTLINE
			.XX ±0.02 [±0.51]	DATE: 02-28-2009	MATERIAL: _____ PROCESS/FINISH: _____
			.XXX ±0.005 [±0.127]	THIRD ANGLE PROJECTION	SIZE DWG NO: C B123 SHEET: 1
			.XXXX ±0.0005 [±0.0127]		
			REMOVE BURRS & BREAK SHARP EDGES .003/015 [0.076/381]		
			CORNER FILLETS .02 [0.51]		
			MACHINED SURFACES INCH mm 3/2		
			mm SHOWN IN [BRACKETS]		