



Resin: Corrosion Grade - Isophthalic Polyester  
 Metallic parts are stainless steel. Float ball is polyethylene.  
 Flanges conform to standard ANSI 150 lb. drill patterns.  
 Standard configuration - single float arm is located on left side,  
 looking into flow unless otherwise noted.

Float Valve shown is to be  
 used for In-Line Application.

FV-S-XWB = Single Arm Valve  
 FV-D-XWB = Double Arm Valve

I.D.	A	B	C	D	E	F	G	K
4"	9-1/2"	7-1/2"	32"	6-5/8"	10-1/8"	20-1/4"	48"	1"
6"	11-1/2"	9-1/2"	32"	7-5/8"	11-1/8"	22-1/4"	48"	1"
8"	14"	11-3/4"	32"	8-7/8"	12-3/8"	24-3/4"	48"	1-1/2"
10"	16-1/2"	14-1/4"	32"	9-7/8"	--	26-3/4"	48"	1-1/2"
12"	19-1/2"	17"	32"	11-3/8"	--	29-3/4"	53"	1-1/2"
14"	21-1/2"	18-3/4"	32"	12-3/8"	--	31-3/4"	53"	1-1/2"
16"	24"	21-1/4"	32"	13-3/8"	--	33-3/4"	53"	2"
18"	25-1/2"	22-3/4"	44"	15"	--	48"	60"	4"
20"	28"	25"	44"	16"	--	48"	60"	4"
24"	32-1/2"	29-1/2"	44"	18"	--	48"	60"	4"

## MER-MADE FILTER

PO Box 306 Denmark, SC 29042  
 P: 803-793-4265 F: 803-793-4332  
[www.meremade.com](http://www.meremade.com)

Customer:

Project: \_\_\_\_\_ Dwg. T-11480

FV-S-XWB or FV-D-XWB Float Valve Rev. 11-14