



High Quality Decorative Protective Sealers.

DESCRIPTION & USE

Multicoat's ACRATHANE COLORSEAL consists of a series of high quality waterbase modified resins that provide a high quality, durable seal on masonry, cementitious, and other building substrates. Colors are factory blended to insure uniformity.

ACRATHANE COLORSEAL is designed for application to a variety of Multicoat's Systems, most notably the KRETE KOTE System. It provides a tough, color consistent, durable and wear resistant protection to surfaces subject to heavy foot and moderate vehicular traffic. Ideally suited for pool decks.

ACRATHANE CLEARSEAL is also a water base material. Not typically used in Colorseal applications, however it can be used to achieve a glossy, wet look. Is also used in conjunction with MULTI-STAIN to lock in the color. CLEARSEAL can also be used on most masonry and stone substrates.

ADVANTAGES:

- Long Wearing
- Enhances Appearance
- Easy to Clean
- Multiple Color Availability
- Weather Resistant
- Water Base - Green Friendly
- Ideal for Re-Sealing Old Kool-Deck
- Chemical Resistant for Pool Decks

SEE TEST DATA

SURFACE PREPARATION

Substrate must be structurally sound and free from grease, oil, dirt, dust, sealers, water repellents and other foreign materials which may interfere with proper bonding. Surface must be completely dry prior to COLORSEAL or CLEARSEAL application.

Multicoat KRETE KOTE and TOP COAT must be allowed to set up and cure for at least 24 to 48 hours before COLORSEAL application. New concrete should be allowed to cure for a minimum of 20 days, and be free from curing compounds, release agents if any, and other water repellent materials which may prevent proper bonding. Do not use on treated lumber.



ONE GALLON CANS
FIVE GALLON PAILS



APPLY DILUTED FIRST COAT OF
ACRATHANE COLORSEAL WITH ROLLER.



SECOND COAT (FULL STRENGTH COAT)
CAN BE APPLIED BY AIRLESS SPRAYER
OR ROLLER.



CLEARSEAL GOES ON WHITE AND
DRIES TO A CLEAR FILM IN MINUTES.
CAN BE ROLLED OR SPRAYED.

ACRATHANE COLORSEAL/CLEARSEAL

