



PRO SERIES® Stain & Scale Control™ Instructions

Note: Cationic polymers used in many clarifiers, flocculants and polyquat algaecides should not be dosed to swimming pool water at the same time as metal control products. Cloudy water, precipitation and reduced product effectiveness may result. Wait 24 hours between additions.

Directions for use:

This product is designed for use in properly balanced pool water.

Initial Dose: Add 1L per 38,000 litres of pool water evenly around the edges. If water hardness level is above 400ppm (parts per million), metal readings are above 0.5ppm, or if being used during start-up of a new plaster pool, wait 24 hours and add a second initial dose.

Maintenance Dose for Scale Control- MONTHLY: Add 150mL per 38,000 litres of pool water per month.

Maintenance Dose for Metal Control- WEEKLY: Add 120mL per 38,000 litres of pool water per week.

Do not add product within 2 days of adjusting calcium hardness or during a full pool acid bath.

For new, remodeled or refinished pools: Add 1.89L per 38,000 litres. Add product to the pool water evenly around the edges after pool is full to reduce the chance of plaster dust formation, scaling, and metal staining. Balance pool water as needed (wait two days before adjusting calcium hardness).

Do not exceed recommended dose.

PRO SERIES Stain & Scale Control can be used in any type of pool and with all types of commercial pool sanitizing systems. It has no adverse effects on water chemistry.

Do not use with biguanides