SAFETY DATA SHEET

Revision Number 1

Issuing Date No data available

Revision Date 24-Oct-2014



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is @ 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE **COMPANY/UNDERTAKING**

Product identifier

Product Name INDICATOR SOLUTION #5

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Swimming Pool Repair & Maintenance

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Poolmaster

Supplier Address 770 Del Paso Road

> Sacramento California 95834 US

Supplier Phone Number Phone:916.567.9800

Fax:916.567.9880

Contact Phone9165679800

Supplier Email Purchasing@poolmaster.com

Emergency telephone number 24 HOUR EMERGENCY NUMBER (CHEM-TEL): USA, Canada, Puerto Rico

800-255-3924

Outside North America Continent 813-248-0585 (Call Collect If

Necessary)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation Category 2



Flammable liquids Category 3

GHS Label elements, including precautionary statements

Emergency Overview

Signal word

Warning

Hazard Statements

Causes serious eye irritation Flammable liquid and vapor



Appearance Blue Physical State Liquid Odor Rubbing alcohol

Precautionary Statements - Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Precautionary Statements - Response

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

(II)

Page 2/12

Unknown Toxicity

0.34% of the mixture consists of ingredient(s) of unknown toxicity

Other information

PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazard	CAS#	Name	Weight - %	PEL	TLV
Yes	62625-28-9	Bromophenol Blue, Sodium Salt	0.1	None Established	None Established
Yes	10102-17-7	Sodium Thiosulfate, Pentahydrate	0.24	None Established	None Established
Yes	67-63-0	Isopropyl Alcohol	15-16	400ppm (980mg/m3)	400ppm (980mg/m3)
No	7732-18-5	Distilled Water	84-85	None Established	None Established

4. FIRST AID MEASURES

First aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention

if irritation develops and persists.

Skin Contact Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, (trained personnel should) give oxygen.

Ingestion Rinse mouth immediately and drink plenty of water. Never give anything by mouth

to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take

precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

(U)

Most Important Symptoms and Burning sensation.

Effects

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, CO2, water spray or regular foam. Use water spray or fog; do not use straight streams.

Unsuitable extinguishing media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Some may be transported hot.

Uniform Fire Code Irritant: Liquid

Flammable Liquid: I-C

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

U

Page 4/12

1141660 - INDICATOR SOLUTION #5 Revision Date 24-Oct-2014

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Evacuate personnel to safe areas. See section 8 for more information. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the

product must be grounded. Do not touch or walk through spilled material.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental Precautions

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for ContainmentA vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth,

sand or other non-combustible material and transfer to containers.

Methods for cleaning up

Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for

later disposal. Soak up with inert absorbent material. Pick up and transfer to properly

labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Do not eat, drink or smoke when using this product. Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area

equipped with sprinklers. Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national

regulations. Store in accordance with local regulations.

Incompatible Products Strong oxidizing agents. Acids. Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

U

Page 5/12

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isopropyl alcohol	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm 10% LEL
67-63-0	TWA: 200 ppm	TWA: 980 mg/m ³	TWA: 980 mg/m ³
		(vacated) TWA: 400 ppm	TWA: 400 ppm
		(vacated) TWA: 980 mg/m ³	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m ³
		(vacated) STEL: 1225 mg/m ³	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face ProtectionNone required for consumer use. If splashes are likely to occur:. Tight sealing safety

goggles.

Skin and Body Protection Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant

apron. Impervious gloves. Antistatic boots.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State Liquid Appearance Blue

AppearanceBlueOdorRubbing alcoholColorNo information availableOdor ThresholdNo information available

Property Values Remarks Method

рH **UNKNOWN** None known Melting / freezing point No data available None known Boiling point / boiling range 100 °C / 212 °F None known **Flash Point** 35 C / 95 F None known **Evaporation Rate** No data available None known Flammability (solid, gas) No data available None known Flammability Limit in Air



Upper flammability limit No data available Lower flammability limit No data available Vapor pressure No data available None known Vapor density No data available None known **Specific Gravity** No data available None known Water Solubility Soluble in water None known None known Solubility in other solvents No data available Partition coefficient: n-octanol/waterNo data available None known **Autoignition temperature** No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known **Dynamic viscosity** No data available None known **Explosive properties** No data available **Oxidizing Properties** No data available

Other Information

Softening Point
VOC Content (%)
Particle Size
No data available
No data available
No data available

Particle Size Distribution

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents. Acids. Chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.



Page 7/12

Eye Contact Specific test data for the substance or mixture is not available. Expected to be an irritant

based on components. May cause redness, itching, and pain. May cause temporary eye

irritation.

Skin Contact Specific test data for the substance or mixture is not available. May cause irritation.

Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Isopropyl alcohol 67-63-0	= 4396 mg/kg (Rat)	= 12800 mg/kg (Rabbit)	= 16000 ppm (Rat) 8 h

Information on toxicological effects

Symptoms May cause redness and tearing of the eyes.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Isopropyl alcohol		Group 3		X
67-63-0				

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposureNo information available.

Chronic Toxicity No known effect based on information supplied.

Target Organ Effects Eyes. Respiratory system. Skin. Blood. Kidney. Liver. Spleen. Systemic Toxicity.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

27,475.00 mg/kg

(U)

ATEmix (dermal)

80,000.00 mg/kg (ATE) **ATEmix (inhalation-vapor)**

347.57 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Isopropyl alcohol	96h EC50: > 1000 mg/L	96h LC50: > 1400000 μg/L		48h EC50: = 13299 mg/L
67-63-0	(Desmodesmus subspicatus)	(Lepomis macrochirus) 96h		
	72h EC50: > 1000 mg/L	LC50: = 11130 mg/L		
	(Desmodesmus subspicatus)	(Pimephales promelas) 96h		
	, ,	LC50: = 9640 mg/L		
		(Pimephales promelas)		

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Isopropyl alcohol	0.05
67-63-0	

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methodsThis material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated PackagingDispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 133

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Isopropyl alcohol	Toxic
67-63-0	Ignitable

14. TRANSPORT INFORMATION

DOT NOT REGULATED



1141660 - INDICATOR SOLUTION #5 Revision Date 24-Oct-2014

TDG Not regulated

<u>MEX</u>

UN-No. UN1993

Proper Shipping Name FLAMMABLE LIQUID, N.O.S.

Hazard Class 3
Packing Group III

Description UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPYL ALCOHOL), 3, III

ICAO

UN-No. UN1993

Proper Shipping Name FLAMMABLE LIQUID, N.O.S.

Hazard Class 3
Packing Group |||

Description UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPYL ALCOHOL), 3, III

IATA

UN-No. UN1993

Proper Shipping Name FLAMMABLE LIQUID, N.O.S.

Hazard Class 3
Packing Group III

Description UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPYL ALCOHOL), 3, III

IMDG/IMO

UN-No. UN1993

Proper Shipping Name FLAMMABLE LIQUID, N.O.S.

Hazard Class 3
Packing Group III
EmS-No. F-E. S-E

Description UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPYL ALCOHOL), 3, III, FP 35C

RID

UN-No. UN1993

Proper Shipping Name FLAMMABLE LIQUID, N.O.S.

Hazard Class 3
Packing Group III
Classification code F1

Description UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPYL ALCOHOL), 3, III

<u>ADR</u>

UN-No. UN1993

Proper Shipping Name FLAMMABLE LIQUID, N.O.S.

Hazard Class 3
Packing Group III
Classification code F1

Description UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPYL ALCOHOL), 3, III

<u>ADN</u>

UN-No. UN1993

Proper Shipping Name FLAMMABLE LIQUID, N.O.S.

Hazard Class 3
Packing Group III
Classification code F1

Special Provisions 274, 601, 640E

Description UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPYL ALCOHOL), 3, III



Hazard Labels3Limited QuantityLQ7VentilationVE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Isopropyl alcohol - 67-63-0	67-63-0	10 - 30	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard No
Fire Hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Isopropyl alcohol	Х	Х	X	X	İ
67-63-0					İ

International Regulations

Mexico

National occupational exposure limits



Page 11/12

Component	Carcinogen Status	Exposure Limits
Isopropyl alcohol		Mexico: TWA 400 ppm
67-63-0 (10 - 30)		Mexico: TWA 980 mg/m ³
		Mexico: STEL 500 ppm
		Mexico: STEL 1225 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

B2 - Flammable liquid D2B - Toxic materials



16. OTHER INFORMATION

NFPA Health Hazards 2 Flammability 3 Instability 0 Physical and Chemical Hazards - HMIS Health Hazards 2 Flammability 3 Physical Hazard 0 Personal Protection

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Revision Date 24-Oct-2014

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

U