



## PORTLAND CEMENT

Mixed with aggregate and other ingredients to make concrete mix, mortar mix and base coat stucco. Available in Type I, Type I/II, Type II and Type III.

To make Concrete Mix:

- 3 Parts Gravel
- 2 Parts All-Purpose Sand
- 1 Part Portland Cement (by volume)

To make Type S Mortar Mix:

- 3½ to 4½ Parts Masonry Sand
- ½ Part Hydrated Lime
- 1 Part Portland Cement (by volume)

Meets the requirements of ASTM C 150 and Federal Specifications for Portland cement.

Item No.	Package Size	Metric	Quantity
1124-31	31 lb. bag	14.1 kg	100/pallet
1124-47	47 lb. bag	21.3 kg	63/pallet
1124-94	94 lb. bag	42.6 kg	35/pallet
1124-42	92.6 lb. bag	42 kg	35/pallet



## MASONRY CEMENT

Available in Type N and Type S masonry cement.

To make Type N Mortar Mix:

- 3 Parts Masonry Sand
- 1 Part Type N Masonry Cement (by volume)

To make Type S Mortar Mix:

- 3 Parts Masonry Sand
- 1 Part Type S Masonry Cement (by volume)

Meets the requirements of ASTM C 91 and Federal Specifications for masonry cement.

Item No.	Package Size	Metric	Quantity
<b>Type S</b>			
1125-71	70 lb. bag	31.7 kg	40/pallet
<b>Type N</b>			
1125-70	70 lb. bag	31.7 kg	40/pallet



## PORTLAND-LIME CEMENT

Blend of Portland cement and hydrated lime meeting the Type S proportions.

Available Regionally.

To make Type S Mortar Mix:

- 2½ to 3 Parts Masonry Sand
- 1 Part Portland-Lime Cement (by volume)

Meets the requirements of ASTM C 91 and Federal Specifications for masonry cement.

Item No.	Package Size	Metric	Quantity
1125-21	70 lb. bag	31.7 kg	40/pallet



## PREMIUM PLASTERING CEMENT

Properly proportioned blend of Portland cement with air entraining and plasticized admixtures for use in base coat and finish coat mixes. Formulation provides improved workability, reduced shrinkage and low-sag characteristics.

Available Regionally.

Meets the requirements of ASTM C 91 and Federal Specifications for masonry cement.

Item No.	Package Size	Metric	Quantity
1125-98	94 lb. bag	42.6 kg	35/pallet



## STUCCO CEMENT

Blended cement designed for use with plaster sand to make base coat stucco and finish coat stucco mixes.

Available Regionally.

To make base coat stucco mix:

- 3-4 parts plaster sand (ASTM C 897)
- 1 part stucco cement (by volume)

Meets the requirements of ASTM C 91

Item No.	Package Size	Metric	Quantity
1201-85	80 lb. bag	36.2 kg	42/pallet



## PLASTIC CEMENT

Blended cement specifically designed for use with plaster sand to make Base Coat Stucco. Available Regionally.

To make Scratch and Base Coat Stucco Mix:

- 3 to 4 Parts Plaster Sand
- 1 Part Plastic Cement (by volume)

Meets the requirements of ASTM C 1328 Type M and S.

Item No.	Package Size	Metric	Quantity
2121-94	94 lb. bag	42.6 kg	35/pallet

May 1980 Introduces color-coded pails for QUIKRETE® Repair Products

1981



30<sup>th</sup> Plant

June 1982 First QUIKRETE® Profit Manual

