

CONCRETE REPAIR & WATERPROOFING



CONCRETE RESURFACER

A special blend of Portland cement, sand, polymer modifiers and other additives. Designed to provide a shrinkage compensated repair material for making thin repairs to sound concrete in need of surface renewal. Can be squeegee, trowel or brush applied. **Use For:**

- Sidewalks
- Driveways
- Floors
- Pool decks
- Patios
- Curbs
- Concrete floors
- Parking decks

| Item No. | Package Size | Metric | Quantity |
|----------|--------------|---------|----------------|
| 1131-20 | 20 lb. pail | 9.1 kg | 60/pallet |
| 1131-40 | 40 lb. bag | 18.1 kg | 64/pallet |
| 1131-40 | 40 lb. bag | 18.1 kg | 35/mini pallet |
| 1131-80 | 80 lb. bag | 36.2 kg | 42/pallet |



SAND/TOPPING MIX

Consists of a uniformly blended mixture of Portland cement, graded sand and other approved ingredients.

Use For:

- Repairing and topping damaged concrete surfaces less than 2 inches thick
- As a base for laying flagstone and paving bricks

| Item No. | Package Size | Metric | Quantity |
|----------|--------------|---------|-----------|
| 1103-10 | 10 lb. bag | 4.5 kg | 6/bale |
| 1103-40 | 40 lb. bag | 18.1 kg | 80/pallet |
| 1103-60 | 60 lb. bag | 27.2 kg | 56/pallet |
| 1103-80 | 80 lb. bag | 36.2 kg | 42/pallet |



VINYL CONCRETE PATCHER

Multi-purpose concrete repair material with strong adhesive properties. Trowels to a feather edge of 1/16". Made of a special blend of exterior grade vinyl resin, fine sand, and Portland cement. Just add water. Available in gray and white.

Use For:

- Making smooth repairs to cracked or chipped concrete floors, sidewalks or steps

| Item No. | Package Size | Metric | Quantity |
|----------|--------------|---------|----------------|
| 1133-11 | 10 lb. pail | 4.5 kg | 4/case |
| 1133-20 | 20 lb. pail | 9.1 kg | 60/pallet |
| 1133-40 | 40 lb. bag | 18.1 kg | 64/pallet |
| 1133-40 | 40 lb. bag | 18.1 kg | 35/mini pallet |



QUICK-SETTING CEMENT

Specially formulated to set in approximately 10–15 minutes. Can be molded or sculpted into place. **Use For:**

- Making concrete repairs where rapid setting is required
- Ideal for repairing broken edges of concrete steps and curbs

| Item No. | Package Size | Metric | Quantity |
|----------|--------------|---------|-----------|
| 1240-11 | 10 lb. pail | 4.5 kg | 4/case |
| 1240-20 | 20 lb. pail | 9.1 kg | 60/pallet |
| 1240-50 | 50 lb. bag | 22.7 kg | 64/pallet |



ANCHORING CEMENT - EXTERIOR USE

A pourable rapid setting expansive cement that develops strength greater than concrete. Sets in 10-30 minutes. Expands as it hardens to fill voids and lock itself securely into place. Suitable for wet environments. **Use For:**

- Setting bolts, handrails, or anything metal to be anchored in concrete
- Ideal for repairing loose wrought iron railings
- Can be used for interior or exterior applications

| Item No. | Package Size | Metric | Quantity |
|----------|--------------|---------|-----------|
| 1245-11 | 10 lb. pail | 4.5 kg | 4/case |
| 1245-20 | 20 lb. pail | 9.1 kg | 60/pallet |
| 1245-60 | 50 lb. pail | 22.7 kg | 64/pallet |

1984



40th Plant

August 1985 Secures Don Knotts as spokesperson. Publishes *Build & Repair With Concrete*



March 1988 Introduces Fast-Setting Concrete Mix

