CONCRETE REPAIR & WATERPROOFING



CONCRETE RESURFACER

A special blend of Portland cement, sand, polymer modifiers and other additives. Designed to provide a shrinkage compensated repair material for making thin repairs to sound concrete in need of surface renewal. Can be squeegee, trowel or brush applied. Use For:

- Sidewalks • Floors • Driveways • Curbs
- · Pool decks · Patios
- Parking decks Concrete floors

Item No.	Package Size	Metric	Quantity
1131-20	20 lb. pail	9.1 kg	60/pallet
1131-40	40 lb. bag	18.1 kg	64/pallet
1131-40	40 lb. bag	18.1 kg	35/mini pallet
1131-80	80 lb. bag	36.2 kg	42/pallet

	TOPPII le Arena Para	NG MIX
	Kar	11=
ust Add Water!	AP	stream on Loss Sound And
and the family of the second state	DA	CONTRACT CONTRACTOR

SAND/TOPPING MIX

Consists of a uniformly blended mixture of Portland cement, graded sand and other approved ingredients.

Use For:

- · Repairing and topping damaged concrete surfaces less than 2 inches thick
- · As a base for laying flagstone and paving bricks

Item No.	Package Size	Metric	Quantity
1103-10	10 lb. bag	4.5 kg	6/bale
1103-40	40 lb. bag	18.1 kg	80/pallet
1103-60	60 lb. bag	27.2 kg	56/pallet
1103-80	80 lb. bag	36.2 kg	42/pallet



VINYL CONCRETE PATCHER

Multi-purpose concrete repair material with strong adhesive properties. Trowels to a feather edge of 1/16". Made of a special blend of exterior grade vinyl resin, fine sand, and Portland cement. Just add water. Available in gray and white. Use For:

· Making smooth repairs to cracked or chipped concrete floors, sidewalks or steps

Item No.	Package Size	Metric	Quantity
1133-11	10 lb. pail	4.5 kg	4/case
1133-20	20 lb. pail	9.1 kg	60/pallet
1133-40	40 lb. bag	18.1 kg	64/pallet
1133-40	40 lb. bag	18.1 kg	35/mini pallet



QUICK-SETTING CEMENT

Specially formulated to set in approximately 10-15 minutes. Can be molded or sculpted into place. Use For:

· Making concrete repairs where rapid setting is required

• Ideal for repairing broken edges of concrete steps and curbs

Item No.	Package Size	Metric	Quantity
1240-11	10 lb. pail	4.5 kg	4/case
1240-20	20 lb. pail	9.1 kg	60/pallet
1240-50	50 lb. bag	22.7 kg	64/pallet




ANCHORING CEMENT - EXTERIOR USE

A pourable rapid setting expansive cement that develops strength greater than concrete. Sets in 10-30 minutes. Expands as it hardens to fill voids and lock itself securely into place. Suitable for wet environments. Use For:

· Setting bolts, handrails, or anything metal to be anchored in concrete

- · Ideal for repairing loose wrought iron railings
- · Can be used for interior or exterior applications





7

August 1985 Secures Don Knotts as spokesperson. Publishes Build & Repair With Concrete



March 1988 Introduces Fast-Setting Concrete Mix

DUIKKEI