SEALERS & ADDITIVES



CONCRETE & MASONRY WATERPROOFING SEALER - NATURAL LOOK

Water based, penetrating, silane/siloxane sealer waterproofs and protects concrete, brick, masonry, pavers and stucco surfaces. Clear sealer does not change the surface appearance. Seals from water, salts and oils. UV Resistant. Interior or exterior use. Wait 30 days before applying to new concrete surfaces.

Use for sealing:

- Driveways
- Patios
- Stucco
- Walls • Sidewalks
 - Floors · Pavers • Bricks

• Steps

| ltem No. | Package Size | Metric | Quantity |
|----------|---------------|--------|-----------|
| 8800-05 | 1 gal. bottle | 3.8 L | 4/case |
| 8800-07 | 5 gal. pail | 18.9 L | 36/pallet |



CONCRETE & MASONRY HIGH GLOSS SEALER - WET LOOK

Water based siliconized-acrylic clear sealer waterproofs, protects and enhances the color of concrete, masonry, brick, paver and natural stone surfaces. Seals from acids, grease, food stains, oil, salt and more. UV resistant. Interior or exterior use. Wait 30 days before applying to new concrete surfaces.

| Item No. | Package Size | Metric | Quantity |
|----------|---------------|--------|-----------|
| 8800-06 | 1 gal. bottle | 3.8 L | 4/case |
| 8800-08 | 5 gal. pail | 18.9 L | 36/pallet |



- Decorative concrete
- Exposed Aggregate
- · Pavers Natural Stone • Brick • Stucco • Steps
- Floors



ACRYLIC CONCRETE CURE & SEAL -SATIN FINISH

Water based, clear acrylic coating cures freshly placed concrete and seals concrete and masonry surfaces.

Features and benefits include:

· Eliminates the need for water curing freshly placed concrete. · Protects and seals from acids, grease, oils, food stains, salt and more.

Meets the requirements of ASTM C 309

| ltem No. | Package Size | Metric | Quantity |
|----------|---------------|--------|-----------|
| 8730-02 | 1 gal. bottle | 3.8 L | 4/case |
| 8730-03 | 5 gal. pail | 18.9 L | 36/pallet |

| / | 0 | - |
|---|------------------|---|
| | CRETI ADMISIN | |
| | - | |

CONCRETE BONDING ADHESIVE

Permanently bonds new concrete, plaster, and stucco to existing concrete, plaster or stucco. Eliminates the need for roughing the surface before the application. Use For:

- · Bonding applications on concrete overlays 1" or thicker
- · Interior and exterior applications

Meets the performance requirements of ASTM C 1059 Type I & II



January 1997 Launches

first website

CONCRETE ACRYLIC FORTIFIER

Acrylic resin admixture designed to enhance bonding and water resistance of concrete patching materials, stucco, surface bonding cement, thin-set mortars and tile grouts. Use To:

- · Improve bonding to existing surfaces
- Eliminate moist curing in most circumstances
- · Reduce permeability
- Meets the requirements of ASTM C 1438

| ltem No. | Package Size | Metric | Quantity |
|----------|---------------|--------|-----------|
| 9902-14 | 1 qt. bottle | 946 mL | 12/case |
| 9902-01 | 1 gal. bottle | 3.8 L | 4/case |
| 9902-05 | 5 gal. pail | 18.9 L | 36/pallet |

| Item No. | Package Size | Metric | Quantity |
|----------|---------------|--------|-----------|
| 8610-14 | 1 qt. bottle | 946 mL | 12/case |
| 8610-01 | 1 gal. bottle | 3.8 L | 4/case |
| 8610-05 | 5 gal. pail | 18.9 L | 36/pallet |



