

- High solids, high gloss epoxy pool paint
- For bare concrete, fiberglass, plaster and previously painted epoxy.
- Up to 3 years service life
- Great for Koi ponds, hot tubs, spas and fountains.
- VOC compliant in US and Canada



EP Epoxy cures to a hard, tough, durable finish, providing stain, chemical and abrasion resistance for protection of concrete, plaster and fiberglass swimming pools, spas and slides. EP Epoxy cures to a high gloss-finish with excellent coverage rates, especially on previously painted epoxy surfaces. EP Epoxy has been a proven performer for more than 50 years. Because of their chemical cure, epoxies are the paints of choice for indoor pools.

PHYSICAL DATA

VEHICLE TYPE: Epoxy Polyamide
 FINISH: High Gloss
 COLORS:
 AquaGreen, White, Black, Dawn Blue, Monument Gray,
 Dark Blue, Vermillion, Royal Blue
 COMPONENTS: 2
 Mix Ratio 2:1 by volume A:B
 Pot Life—8 Hours
 CURING MECHANISM: Chemical Cure
 SOLIDS (theoretical):
 By weight...73 +/- 2%
 By volume...60 +/- 3%
 COVERAGE: 500 sq. ft/gal.
 VOC: 340 g/l max. (as supplied)
 FLASH POINT: 60°F (SETA)

APPLICATION DATA

METHOD: Brush, Use no thicker than 3/8" Mohair or Lambskin Roller, Airless or Conventional Spray.
 NUMBER OF COATS: 2 (Product is self-priming)
 DRY FILM THICKNESS PER COAT: Minimum 1.7 mils; 2.9 wet mils. Maximum 2 mils; 3.3 wet mils.
 APPLICATION TEMP: 50° F. Min. / 90°F. Max.
 DRY TIME* 5-7 Days Outdoor pool to fill pool
 10-14 Days Indoor pool to fill pool
 To Recoat: 12-72 Hours
 THINNER:
 Ramuc Thinner