

System:2™ Mod Media™ Filters—PLM Series by Sta-Rite®



Greater dirt-loading capacity reduces maintenance

The System:2 Mod Media filter is ideal for small inground and aboveground pools. This filter is a compact adaptation of System:3® filter technology from Sta-Rite, so it handles dirt loads up to 15 times greater than sand filters of equivalent size. The result: You capture more dirt between cleanings and minimize time on maintenance.

- Rugged composite construction resists corrosion and weathering.
- Compact design fits in tight installations and can be easily shielded from view.
- Balanced-flow tank design works in unison with the high-capacity filter module to collect dirt over its entire surface—holds more dirt so you clean less often.
- Less frequent cleaning also increases filter module service life and lowers lifetime costs.



System:2™ Mod Media™ Filters—PLM Series



Top-mounted pressure gauge and information panels are positioned for easy reading

Split-tank design permits simple, thorough, rinse-in-place cleaning to save time

Posi-Ring® closure is easy to secure, lasts for years

Balanced-flow tank hydraulics direct water through each side of the filter module for uniform dirt loading to prevent clogging and maximize filtration effectiveness



Easy to clean—just spray and go



The Mod Media filter contains a one-piece module that simply drops into an easily accessible tank. When cleaning is necessary, just remove the lid (no tools are necessary) and spray-rinse the module while it is still in place.* It only takes minutes to thoroughly clean the filter and get back into service—fast.



Less maintenance . . . YES!

The balanced-flow tank design directs water through both sides of the filter module, which increases dirt-loading without clogging. Holding more dirt means a longer time between cleanings.

*Modules used in conjunction with certain pool/spa sanitizers may require soaking in special cleaning solutions

System Performance

Model	For Pools up to (Gal.) 8 Hr. Turnover	Filter Area (Sq. Ft.)	Flow Rate ¹ (GPM)
PLM100	48,000	100	38–100
PLM125	60,000	125	47–125
PLM150	72,000	150	56–150
PLM175	72,000	175	66–150
PLM200	72,000	200	75–150
PLM300	72,000	300	113–150

¹Based on NSF-recommended flow rate for commercial at 0.375 GPM per square foot.

Operating Limits —Maximum continual operating pressure is 50 psi. For pool/spa (bather) applications, the maximum operating water temperature within the filter is 104°F (40°C).

Available from:



Simply Smarter.

www.staritepool.com

Phone: 800-831-7133



pumps / filters / heaters / heat pumps / automation / lighting / cleaners / sanitizers / water features / maintenance products

All Pentair trademarks and logos are owned by Pentair or one of its global affiliates. Sta-Rite®, System:2™, System:3®, Mod Media™ and Posi-Ring® are trademarks and/or registered trademarks of Pentair Water Pool and Spa, Inc. and/or its affiliated companies in the United States and/or other countries. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.