

Steady water temperatures. Total comfort. All year long.

Enjoy the ultimate swimming experience—any time of day or year—with THERMEAU®'s smart pool heating and cooling management system.





PRESTIGE

Increase the value of your pool and spa with THERMEAU®.

Invest in comfort all year long with THERMEAU®'s PRESTIGE residential heat pump. PRESTIGE has been designed specifically for home owners looking for optimal pool and spa temperatures, regardless of the time of day or year, as well as low energy bills and maintenance costs.

PRESTIGE is based on our sophisticated and renowned technology that is used in outdoor commercial pools across North America. You'll gain peace of mind knowing that you are getting the very best in performance and reliability.

THE THERMEAU® ADVANTAGE

- Unequalled energy efficiency
- Triple-action sound barrier
- High-precision electronic temperature control
- Quick and easy installation
- Minimal and efficient maintenance
- Ultra-high-performance components



Smart heating and cooling management system

Developed and tested in Canada, where extreme temperature variations occur, THERMEAU®'s products have been proven to perform in both frigid and sweltering hot weather conditions. PRESTIGE's innovative **smart heating and cooling management system** is a total game changer for residential pool and spa owners. You'll not only benefit from optimal and constant temperature levels but also avoid extreme changes in temperature, which can cause high energy costs—and premature and progressive deterioration of your equipment. Safeguard your pool or spa investment with THERMEAU®'s PRESTIGE.



Premium-quality components. Ingenious design. Outstanding performance.



The **Gold** evaporator fin provides corrosion resistance for application near seacoast and for utmost durability and performance.





Copeland scroll compressor

- The best scroll compressor in the industry
- Unmatched reliability and durability in any climate and in all weather conditions
- The quietest system on the market
- Impressive combination of performance and energy savings
- Quality components that require little maintenance



Ultra-silent pool heating and cooling thanks to its triple-action **sound barrier system**.



Electronic **temperature control** with auto-diagnostic features



Rifled **titanium tube** increases the exchange surface for better heat transfer. Extremely robust, it withstands the pool's chemical products.



TH105 - TH125 - TH140B



Two-inch union at the front of the heat pump for easy installation.



A renowned warranty program you can trust

THERMEAU®'s products not only exceed the industry's highest standards but also come with a rock-solid warranty program to give you added peace of mind. What's more: benefit from outstanding customer and after-sales service that is second to none.



5-year warranty on labor



5-year warranty on parts



10-year limited warranty on our heat exchanger



Large, quiet ventilation system with a brilliantly designed profiled blade that improves airflow and minimizes noise



Direct flow union drains water caused by condensation. No more wet pavement!



Lockable panel that secures the system's configuration and protects it from bad weather



Removable protective grille for easy cleaning and maintenance.



Features

Choose between one of our top-performing models.

OPERATING SPECIFICATIONS	TH105	TH125	TH140B	
Volts	230	230	230	
Hertz	60	60	60	
Phase	1	1	1	
Compressor amps	23.2A	24.3A	27.3A	
Cooling	Yes	Yes	No	
Heat exchanger	Titanium / PVC	Titanium / PVC	Titanium / PVC	
Fan motor max. load amps	2.4A	2.4A	2.4A	
Fan motor HP	1/3	1/3	1/3	
Fan motor speed	825 RPM	825 RPM	825 RPM	
Minimum circuit ampacity	40 A	42.5 A	42.5 A	
Maximum fuse	60 A	60 A	60 A	
Compressor	Copeland scroll	Copeland scroll	Copeland scroll	
TEST PERFORMANCES				
80F amb, 80F water, 80% RH	105,000 BTU/h	121,000 BTU/h	133,000 BTU/h	
COP	6	5.5	6	
80F amb, 80F water, 63% RH	100,000 BTU/h	116,000 BTU/h	126,000 BTU/h	
COP	5.8	5.3	5.8	
50F amb, 80F water, 63% RH	70,000 BTU/h	80,000 BTU/h	87,000 BTU/h	
COP	4	4	4	
Defrost	Hot gas	Hot gas	Hot gas	
Refrigerant	R-410A	R-410A	R-410A	
Optimal water flow rate (GPM)	40	55	60	
Max. water flow rate (GPM)	100	100	100	
Max. water temperature	104F	104F	104F	
Net Weight (lbs)	230	245	265	
Shipping Weight (lbs)	275	290	310	
Dimensions (in.)	H: 34 L:33 P:39	H: 34 L:33 P:39	H: 34 L:33 P:39	
Shipping dimensions (in.)	H: 39 L:35 P:44	H: 39 L:35 P:44	H: 39 L:35 P:44	

Models for in-ground pools

Dimensions (ft.)	Surface (ft.²)	Liters	Gallons US	GOOD	BETTER	BEST
12 x 24	288	45,460	11,900	TH105	TH105	TH105
14 X 28	392	61,323	16,200	TH105	TH105	TH105
15 X 30	450	70,092	18,500	TH105	TH105	TH105
16 X 32	512	79,871	21,100	TH105	TH105	TH125
18 X 36	648	102,285	26,700	TH125	TH125	TH140B
20 X 40	800	124,918	33,000	TH140B	TH140B	TH140B

^{*} Also available in TH55 - TH65 - TH85. Contact us for more information.





