

Print Date: 03-16-2015

SAFETY DATA SHEET

3N1 FAST SET WHITE 825362PM

REVISION DATE: 02-19-2015

SUPERSEDES: 10-01-2012

SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER

PRODUCT INFORMATION

PRODUCT: PRODUCT DESCRIPTION: **INTENDED USE:** PRODUCT IDENTIFIER:

3N1 FAST SET WHITE Cement Adhesive 825362PM

COMPANY INFORMATION

H.B. Fuller Construction Products Inc. 1105 S. Frontenac Street Aurora, IL 60504 Phone: 1-800-552-6225

> Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

GHS Hazard Symbols:	
GHS Signal Word:	Danger
GHS Classification:	Serious Eye Damage/Eye Irritation Category 1; Carcinogenicity Category 1A; Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 1; Skin Corrosion/Irritation Category 2
GHS Hazard	Causes skin irritation.; Causes serious eye damage.; May cause cancer.; Causes damage
Phrases:	to organs through prolonged or repeated exposure.
GHS Precautions:	
Safety Precautions: First Aid Measures:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Do no eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Immediately call a POISON CENTER or doctor/physician. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	PERCENT	Classification	Note
Alumina cement	65997-16-2	30 - 50	Eye Dam. 1; H318	
			Skin Irrit. 2; H315	





3N1 FAST SET WHITE 825362PM

Print Date: 03-16-2015

SAFETY DATA SHEET

Crystalline silica	14808-60-7	10 - 30	Carc. 1A; H350 STOT RE 1; H372	* (see below)
Kieselguhr, soda ash flux-calcined	68855-54-9	5 - 10	STOT RE 2; H373	
Cristobalite	14464-46-1	1 - 5	Acute Tox. 4; H332 Carc. 2; H351 STOT RE 1; H372	* (see below)
Calcium hydroxide	1305-62-0	1 - 5	Eye Dam. 1; H318 Skin Irrit. 2; H315 STOT SE 3; H335	* (see below)

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

SECTION 4: FIRST AID MEASURES

IF IN EYES: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist. IF SWALLOWED: Severely irritating. Do not induce vomiting. Seek medical attention immediately. Drink 2 glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person.

SECTION 5: FIRE FIGHTING MEASURES

Use water spray, foam, dry chemical or carbon dioxide. Material will not burn. Persons exposed to products of combustion should wear self- contained breathing apparatus and full protective equipment. Carbon dioxide, Carbon monoxide Sulfur containing gases
Silicon dioxide

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION:	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the
METHODS FOR CLEAN-UP:	quantity of the spill, the area in which the spill occurred. Avoid creating dusts. Eliminate ignition sources. If a vacuum is used, ensure that the material is wetted or otherwise treated so an explosive dust atmosphere is not created within the vacuum.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling:	Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Avoid breathing material.
Storage:	Store in a cool, dry place.



Page 3 of 7

3N1 FAST SET WHITE 825362PM

Print Date: 03-16-2015

SAFETY DATA SHEET

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Crystalline silica	* (see below)	0.025 mg/m3 TWA (respirable fraction)	((250)/(%SiO2 + 5) mppcf TWA (respirable)); ((10)/(%SiO2 + 2) mg/m3 TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust))
Calcium carbonate	* (see below)	No data available.	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
Diatomaceous earth	* (see below)	No data available.	20 mppcf TWA; ((80)/(% SiO2) mg/m3 TWA)
Calcium sulfate	* (see below)	10 mg/m3 TWA (inhalable fraction)	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
Cristobalite	* (see below)	0.025 mg/m3 TWA (respirable fraction)	Not established
Calcium hydroxide	* (see below)	5 mg/m3 TWA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)

ENGINEERING CONTROL METHODS:

VENTILATION:	Use local exhaust ventilation or other engineering controls to minimize exposures.
EYE PROTECTION:	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
SKIN PROTECTION: GLOVES:	Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt. An apron may be appropriate if splashing can occur. Nitrile
RESPIRATORY PROTECTION:	Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with dust/mist filter. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Solid
COLOR:	White
ODOR:	Odorless
ODOR THRESHOLD:	Not established
pH:	Not established
FREEZING/MELTING POINT (deg. C):	Not established
BOILING POINT (deg. C):	Not established
FLASH POINT:	Non flammable
EVAPORATION RATE:	Not established



UPPER EXPLOSIVE LIMIT (% in air):

VAPOR PRESSURE (mm Hg):

WEIGHT PER GALLON (lbs.):

OCTANOL/WATER COEFFICIENT:

AUTOIGNITION TEMPERATURE:

DECOMPOSITION TEMPERATURE:

LOWER EXPLOSIVE LIMIT (% in air):

Print Date: 03-16-2015

FLAMMABILITY:

VAPOR DENSITY:

SOLUBILITY:

VISCOSITY:

SPECIFIC GRAVITY:

SOLIDS (% by weight):

VOC, weight percent

SAFETY DATA SHEET

Not a flammable solid or gas Not established Not established Not established Not established 7.50 0.900 Not established Not established Not established Not established No data available. 100.0 0.00

SECTION 10: STABILITY AND REACTIVITY

STABILITY: CHEMICAL INCOMPATIBILITY: HAZARDOUS POLYMERIZATION:

Stable under normal conditions. Not established Will not occur. HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide Sulfur containing gases Silicon dioxide

SECTION 11: TOXICOLOGICAL INFORMATION

Component Toxicity / Toxicology Data:

Component Toxicity / Toxicology Data:		
COMPONENT NAME	LD50/LC50	
Crystalline silica	ORAL LD50 RAT 500 MG/KG	
Calcium carbonate	ORAL LD50 RAT 6,450 MG/KG	
Calcium sulfate	ORAL LD50 RAT > 3,000 MG/KG	
Fly ash	ORAL LD50 RAT > 2,000 MG/KG	
Calcium hydroxide	ORAL LD50 RAT 7,340 MG/KG	

This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Serious eye damage / irritation :Can cause moderate irritation, tearing and reddening.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: No data available.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: No data available.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: May cause respiratory irritation.

Specific target organ toxicity-repeated exposure: Causes damage to organs through prolonged or repeated exposure.

Target organs potentially affected by exposure: Lungs

Aspiration hazard: No data available.

3N1 FAST SET WHITE 825362PM



Page 5 of 7

Print Date: 03-16-2015

3N1 FAST SET WHITE 825362PM

SAFETY DATA SHEET

Medical Conditions Aggravated by Exposure: Lung disease

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW:	No ecological information available for this product.
MOBILITY:	No data available.
PERSISTENCE:	No data available.
BIOACCUMULATION:	No data available.

This product has not been tested for ecological effects. Relevant information for components is listed below:

Component:	Ecotoxicity values:
Calcium sulfate	Acute Toxicity (Fish): 96 Hr LC50 Lepomis macrochirus: 2980 mg/L [static]; 96 Hr
	LC50 Pimephales promelas: >1970 mg/L [static]
	Acute Toxicity (Daphnia): Not established
	Acute Toxicity (Algae): Not established

SECTION 13: DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Dispose of in an approved landfill. Consult your state, local or provincial authorities and your local waste vendor for more restrictive requirements.

SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transportation information.

US DOT:	NOT REGULATED
IATA:	NOT REGULATED

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS	
U.S. EPA TSCA:	This product is in compliance with the Toxic Substances Control Act's
	Inventory requirements.
CANADIAN CEPA DSL:	The components of this product are included on the DSL or are exempt
	from DSL requirements.
EUROPEAN REACH:	As a result of the introduction of REACH into Europe, this product
	cannot be imported into Europe unless the REACH requirements are
	met.
AUSTRALIA AICS:	This product contains a component that is not on the Australian
	Inventory (AICS).
	from DSL requirements. As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met. This product contains a component that is not on the Australian

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg.request@hbfuller.com to request an export review.

This product contains a chemical substance that is	D-Glucuronic acid, polymer with 6-deoxy-L-	
subject to a Significant New Use Rule (SNUR)	mannose and D-glucose, acetate, calcium	
under Section 5(a)(2) of TSCA:	magnesium potassium sodium salt	
	40 CFR 721.2076 (PMN P-00-0007) (SNUR does not apply if this material is used in a cementitious product)	





3N1 FAST SET WHITE 825362PM

Print Date: 03-16-2015

SAFETY DATA SHEET

FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

 Chemical Name
 CAS#

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System. D2A D2B

STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List		CAS	Percent
Quartz	(Carcinogen)	14808-60-7	10 - 30
Titanium dioxide	(Carcinogen)	13463-67-7	0.01 - 0.1
Acetaldehyde	(Carcinogen)	75-07-0	0.001 - 0.01
Benzene	(Carcinogen)	71-43-2	0.001 - 0.01
Nickel	(Carcinogen)		< 10 ppm
Lithium carbonate	(Developmental toxin)	554-13-2	0.01 - 0.1
Methanol	(Developmental toxin)	67-56-1	0.001 - 0.01
Benzene	(Developmental toxin)	71-43-2	0.001 - 0.01
Toluene	(Developmental toxin)	108-88-3	0.001 - 0.01
Benzene, methyl-	(Female reproductive toxin)	108-88-3	0.001 - 0.01
Benzene	(Male reproductive toxin)	71-43-2	0.001 - 0.01

Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's.

SECTION 16: OTHER INFORMATION

SDS VERSION DATE: 02-19-2015

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 0 REACTIVITY -- 0 See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of



Page 7 of 7

3N1 FAST SET WHITE 825362PM

Print Date: 03-16-2015

SAFETY DATA SHEET

the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.