**Now Available** In 9.75 lb. **Plastic Bags** 

## **TEC® AccuColor® Premium Sanded Grout**

Ensure a flawless finish for your next floor or wall tile project, countertop, or installations with wider grout joints, in high traffic and wet areas, indoors or outdoors, for residential to extra-heavy commercial.

AccuColor® Premium Sanded Grout is a polymer-enhanced, Portland cement grout, formulated to provide highly wear-resistant, color consistent grout joints from  $\frac{1}{8}$ " to  $\frac{1}{2}$ " (3-12 mm). This grout meets ANSI A118.6 Specifications for Commercial Cement Grout, and ANSI A118.7 Specifications when mixed with TEC<sup>®</sup> Acrylic Grout Additive in place of water. It can also contribute to LEED<sup>®</sup> project points, with 0 VOC.

For finishing touches, also consider TEC® AccuColor® Sanded Siliconized Acrylic Caulk. This caulk is precisely color-matched to the 32 AccuColor® Premium Sanded Grout colors.

## AccuColor® Premium Sanded Grout is Available in:

9.75 lb. (4.42 kg) plastic bags (4 bags/case) 25 lb. (11.34 kg) moisture-resistant bags

50 lb. (22.68 kg) moisture-resistant bags (Special Order Size\*)

Custom Colors, in either 25 lb. or 50 lb. sizes<sup>†</sup>

\* Special Orders require a minimum order and 14-day lead time-ask your TEC® representative for more details. <sup>+</sup> Custom Colors require a minimum order and longer lead time—ask your TEC<sup>®</sup> representative for more details.

Visit tecspecialty.com to learn more





Product contains zero VOC.



©Copyright 2016 H.B. Fuller Construction Products Inc. TEC®, the TEC® logo and AccuColor® are registered trademarks of H.B. Fuller Construction Products Inc.

LEED® is a registered trademark of U.S. Green Building Council. FLYTACG N0816-20

Now Available In 9.75 lb. Plastic Bags

## **TEC® AccuColor® Premium Unsanded Grout**

Perfect for projects with delicate tile surfaces, such as marble or natural stones that could be scratched by sanded grout during installation. AccuColor<sup>®</sup> Premium Unsanded Grout is formulated to provide highly wear-resistant, smooth, color consistent, non-shrinking, dense joints, even in hot, dry conditions or with highly absorptive tile. It is designed for small grout joints up to  $\frac{1}{8}$ " (3 mm), typically used for indoor or outdoor walls, wet area enclosures and backsplashes.

AccuColor<sup>®</sup> Premium Unsanded Grout is a polymer-enhanced, Portland cement grout that meets ANSI A118.6 Specifications for Commercial Cement Grout, and ANSI A118.7 Specifications when mixed with TEC<sup>®</sup> Acrylic Grout Additive in place of water. It can contribute to LEED<sup>®</sup> project points, with 0 VOC.

For a flawless finish, also consider TEC<sup>®</sup> AccuColor<sup>®</sup> Unsanded Siliconized Acrylic Caulk. This caulk is precisely color-matched to the 32 AccuColor<sup>®</sup> Premium Unsanded Grout colors.

## AccuColor® Premium Unsanded Grout is Available in:

9.75 lb. (4.42 kg) plastic bags (4 bags/case) 25 lb. (11.34 kg) moisture-resistant bags (Special Order Size\*) Custom Colors, in 25 lb. size<sup>†</sup>

\* Special Orders require a minimum order and 14-day lead time—ask your TEC® representative for more details.

<sup>†</sup> Custom Colors require a minimum order and longer lead time—ask your TEC® representative for more details.

Visit tecspecialty.com to learn more





Product contains zero VOC.

IMAGINE. ACHIEVE.

©Copyright 2016 H.B. Fuller Construction Products Inc. TEC<sup>®</sup>, the TEC<sup>®</sup> logo and AccuColor<sup>®</sup> are registered trademarks of H.B. Fuller Construction Products Inc.

LEED<sup>®</sup> is a registered trademark of U.S. Green Building Council. FLYTACG N0816-20