SAFETY DATA SHEET



Texrite Ac-cent Nonsanded Grout

As	of	date:	August	7,	2015
			0		

Section 1	Product Description
Product Name: Recommended Use: Synonyms:	Ac-cent Nonsanded Grout Nonsanded Grout Unsanded Grout, Latex-polymer tile grout, Latex-polymer joint filler mortar
Manufacturer:	Texas Cement Products, dba Texrite 4000 Pinemont, Houston, Texas 77018, USA 713-682-8411 www.texrite.com
	713-682-8411 (8am-3pm, CST, M-F) 713-688-2488

Classification of the chemical in accordance with paragraph (d) of 1910.1200;

Signal Word:	Danger
GHS Class:	Serious Eye Damage/Eye Irritation, Category 1, Skin Corrosion/Irritation, Category 2 Skin Sensitizer/Allergic skin reaction, Category 1 Carcinogen/May cause cancer if inhaled, Category 1A, May cause respiratory irritation, STOT SE3 Damage to organs through prolonged or repeated exposure if inhaled, STOT RE1
Hazard Statements:	H100s = General, H200s = Physical, H300s = Health, H400s = Environmental
	 -Causes skin irritation. -May cause an allergic skin reaction. -Causes serious eye damage. -Causes cancer if inhaled. -May muse respiratory irritation. -Causes damage to organs through prolonged or repealed exposure if inhaled.
Precautionary Statements:	 -Obtain special instructions before use. -Do not handle until all safety precautions have been read and understood. -Do not breathe dust. -Do not breathe dust. -Wash skin thoroughly after handling. -Do not eat, drink or smoke when using this product. -Use only outdoors or in a well-ventilated area. -Contaminated work clothing should not be allowed out of the workplace -Wear protective gloves and eye, face protection. -P302+P3529, -IF ON SKIN. Wash with plenty of water P304+P340 -IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 -IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 -IF exposed or concerned: Gel medical advice / attention. P312A - Call a POISON CENTER if you feel unwell.

P321A -Specific treatment (see supplementary instructions on this label)

P333+P313 -If skin irritation or rash occurs: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

- P403+P233 -Store in a well-ventilated place. Keep container lightly dosed.
- P405 -Store locked up.
- P501A -Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

Ingredients(s) with unknown acute toxicity: None

Hazards not otherwise classified identified during the classification process: None

Section 3 Composition Information and Ingredients

Mixture:

Component Name	CAS #	WT %	<u>Classification</u>
Portland Cement	65997-15-1	40-60%	STOT SE 3, H335: Eye Dam 1,H318 Skin Sens. 1, H317; Skin Irrit. 2, H315
Titanium dioxide Calcium sulfate Silica Sand	13463-67-7 7778-18 -9 14808-60-7	0.1-5%, 0.1-5% 0.1-5%	Carc. 2, H351 STOT SE 3, H335: Carc. 1A, H350A, STOT RE 1, H372A

Section 4 First-Aid Measures

Emergency and First Aid Procedures

Inhalation:	Remove casualty to fresh air and keep at rest. If breathing is irregular or stopped, administer artificial respiration. In case of inhalation, consult a doctor immediately and show him packing or label.			
Eyes:	IF IN EYES: Rinse cautiously with water with the eyelids open for a sufficient length of time. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation continues, then get medical advice/attention immediately. Protect uninjured eye.			
Skin Contact:		ish with plenty of soap and water. If skin irritation occurs: Get medical Take off contaminated clothing and wash before reuse.		
Ingestion:	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.			
Most Important symptoms/effects, acute and delayed: Eye Irritation Eye damages Skin Irritation Erythema Indication of any immediate medical attention and special treatment needed: In case of accident or unwellness, seek medical advice immediately (show directions for use safety data sheet if possible).				
Section 5	Fire Fighting N	leasures		
Extinguishing Media: Fire Fighting Methods a	nd Protection:	Use carbon dioxide, or water spray when fighting fires involving this material. Firefighters should wear full protective equipment and NIOSH approved self- contained breathing apparatus.		
Fire and/or Explosion H	azards:	Do not inhale explosion and combustion gases. Burning produces heavy smoke.		
Hazardous Combustion Products: Explosive properties: Oxidizing properties:		N.A. N.A. N.A.		

Special protective equipment and precautions for fire-fighters:

Texrite Ac-cent Nonsanded Grout -SDS

Use suitable breathing apparatus. Collected contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

Section 6	Accid	ental Re	lease Meası	ires				
Steps to Take in Case Material Is Released or Spilled:			Wear personal protection equipment.Wear breathing apparatus if exposed to vapors/dusts/aerosols. Provide adequate ventilation. Use appropriate respiratory protection. See protective measures under section 7 and 8. Ventilate the contaminated area. Suitable material for taking up: absorbing material, organic, sand. Wash with plenty of water.					
Section 7	Hand	ling and	Storage					
Handling: Storage:			Exercise th localized ve cleaned. Be incompatibl be changed also section handling. W protection.	entilation syste efore making t le material res d before enter n 8 for recomr Vear protective Keep containe	e when hand em. Don't use ransfer oper iduals in the ing eating ar nended prote e gloves/prot	dling or oper e empty con ations, assu containers. eas. Do not ective equip ective clothi	hing the tainer be re that the Contam eat or do ment. W ng/eye p	container. Use efore they have been here aren't any inated clothing should rink while working. Se ash thoroughly after protection/face
Storage Code:			N.A.					
Section 8 List of compon	Expos ents with OEL valu		trols / Perso	onal Protecti	on			
<u>Component</u>	OEL Type Country	<u>Ceiling</u>	Long Term <u>mg/m3</u>	Long Term <u>ppm</u>	Short Term <u>mg/m3</u>	Short Term <u>ppm</u>	<u>Behavio</u>	<u>r Note</u>
Portland cement	OSHA OSHA ACGIH		15 5.0 1					A4- Not classifiable as a Human Carcinogen; pulmonary function: respiratory symptoms;
Titanium dioxide	OSHA		15					asthma A4- Not classifiable as a Human Carcinogen;
	ACGIH		10					lower tract irritation
Calcium sulfate	OSHA OSHA ACGIH		15 5 10					nasal symptoms
Silica Sand	ACGIH		0.025					A2-SupsectedHuman Carcinogen; lung cancer; pulmonary fibrosi:
Control Parameters Engineering Measures:							perator comfort e dust	
Personal Protective Equipment (PPE): Respiratory Protection: Respirator Type(s): Eve Protection:			under normal conditions of use. Avoid generating airborne dust No respiratory protection required under normal conditions of use. Use NIOSH approved air purifying respirator with dust filter. Wear close fitting safety glasses or goggles when handling this product.					

No respiratory protection required under normal conditions of use. Use NIOSH approved air purifying respirator with dust filter. Wear close fitting safety glasses or goggles when handling this product.

Eye Protection:

Skin Protection:

Gloves:

Avoid skin contact by wearing clothing that provides comprehensive protection. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. PVC, neoprene, rubber, nitrile

Section 9 Physical and Chemical Properties

Appearance:	Powder, various- solid color
Odor:	Cement likes
Odor Threshold:	None
pH (Neutrality):	N.A.
Melting Point/Freezing Point:	N.A.
Boiling Range (Ibp,50%,Dry Point):	N.A.
Flash Point (Test Method):	N.A.
Evaporation Rate	
(n-Butyl Acetate=1):	N.A.
Flammability Classification:	N.A.
Lower Flammable	
Limit in Air (% by vol):	N.A.
Upper Flammable	
Limit in Air (% by vol):	N.A.
Vapor Pressure (mm of Hg)@20 C:	N.A.
VAPOR DENSITY (Air=1):	N.A.
GRAVITY @ 68/68F / 20/20C:	
Specific Gravity (Water=1):	N.A.
Pounds/Gallon:	N.A.
Water Solubility:	Dispersible
Partition Coefficient (n-Octane/Water):	N.A.
Auto Ignition Temperature:	N.A.
Decomposition Temperature:	N.A.
Other Information	
Substance Groups relevant properties	N.A.
Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.

Section 10

Stability and Reactivity

Reactivity: Chemical Stability: Possibility of Hazardous Reaction: Conditions to Avoid: Incompatible Materials: Hazardous Decomposition Products: Stable under normal conditions. No data available None Stable under normal conditions. None in particular None

Section 11 Toxicological Information

Toxicological Information of the mixture: There is no toxicological data available on the mixture. Consider the individual concentrations of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological Information on the main components of the mixture:

Silica Sand	a) acute toxicity	LD50 (Oral): =500 mg/kg (Rat)
Titanium dioxide	a) acute toxicity	LD50 (Oral):>10000 mg/kg (Rat)
Calcium sulfate	a) acute toxicity	LD50 (Oral): >3000 mg/kg (Rat)

If not differently specified, the information required in the regulation and listed below must be considered NA. a) acute toxicity

b) skin corrosion/irritation

	 c) serious eye damage/irrii d) respiratory or skin sensi e) germ cell mutagenicity f) carcinogenicity g),reproductive toxicity h) STOT - single exposure I) STOT -repeated exposure J) aspiration hazard 	itization
Substance(s) listed on the	IARC Monographs: Silica Sand Titanium Dioxide	Group 1 Group 2B
Substance(s) listed as OS		
Substance(s) listed as NIC	OSH Carcinogen(s): Silica Sand Titanium Dioxide	
Substance(s) listed on the	NTP report on Carcinogens Silica Sand	S:

Section 12 Ecological Information

Overview: Adopt good working practices, so that the product is not released Into the environment.

Ecotoxicity:

<u>QTY , Chemical Na</u> me	CAS Number	Eco Toxicity
0.1-5 %, Calcium sulfate	7778-18 -9	LC 50 a) Aquatic acute toxicity Fish Lepomis macrochirus =2980mg/L 96h EPA LC 50 a) Aquatic acute toxicity Fish Pimephales promelas > 1970mg/L 96h EPA
0.1-5 %, Silica Sand	14808-60-7	LC 50 a) Aquatic acute toxicity carp >10000.00000 mg/L 72h
Persistence and degradability:The polyBioaccumulative potential:No datMobility in soil:No datOther Adverse Effects:No dat		ata

Section 13 Disposal Considerations

Disposal Methods:

Dispose in accordance with all applicable Federal, State and Local regulations. Always contact a permitted waste disposer (TSD) to assure compliance. Not Determined

Waste Disposal Code(s):

Section 14 Transport Information

UN number	
ADR-UN number:	N/A
DOT-UN number:	N/A
IATA-UN number:	N/A
IMDG-UN number:	N/A
UN proper shipping name	
ADR-Shipping Name:	N/A
DOT Proper Shipping Name:	N/A
IATA-Technical name:	N/A
IMDG-Technical name:	N/A
Transport hazard class(es)	
ADR- Class:	N/A
DOT Hazard Class:	N/A

IATA- Class:	N/A
IMDG-Class:	N/A
Packing group	
ADR Packing Group:	N/A
DOT-PackIng group:	N/A
IATA-Packing group:	N/A
IMDG-Packing group:	N/A
Environmental hazards	
Marine pollutant:	No
Environmental Pollutant:	N.A.
Transport in bulk according to Annex II of MA	
	N.A.
Special Precautions	
Department of Transportation (DOT):	
DOT-Special Provision(s):	N/A
DOT Label(s):	N/A
DOT Symbol:	N/A
DOT Cargo Aircraft:	N/A
DOT Passenger Aircraft:	N/A
DOT Bulk:	N/A
DOT Non-Bulk:	N/A
Road and Rail (ADR-RID):	
ADR-Label:	N/A
ADR Hazard identification number:	
ADR Tunnel Restriction Code:	N/A
Air (IATA):	N1/A
IATA- Passenger Aircraft:	N/A
IATA- Cargo Aircraft :	N/A
IATA- Label:	N/A
IATA- Subrisk:	N/A
IATA- Erg:	N/A
IATA- Special Provisions:	N/A
Sea (IMDG):	N/A
IMDG -Stowage Code:	
IMDG -Stowage Note: IMDG -Subrisk:	N/A N/A
	N/A N/A
IMDG -Special Provisions: IMDG -Page:	N/A N/A
IMDG -Fage. IMDG -Label:	N/A N/A
IMDG -EMIS:	N/A N/A
IMDG -EMIS. IMDG -MFAG:	N/A N/A
	1.1/1

Section 15

Regulatory Information

USA - Federal regulations

TSCA • Toxic Substances Control Act TSCA Inventory:

All the components are fisted on the TSCA inventory

TSCA listed substances:


Portland cement	is listed in TSCA	Section 8b
Titanium Dioxide	is listed in TSCA	Section 8b
Calcium sulfate Silica Sand	is listed in TSCA is listed in TSCA	Section 8b Section 8b

SARA - Superfund Amendments and Reauthorization Act Section 302 – Extremely Hazardous Substances: no substance listed

Section 304 – Hazardous substances:	no substance listed
Section 313 – Toxic chemical list:	no substance listed

CERCLA – Comprehensive Environmental Substance(s) listed under CERCLA:	Response, Compensations, and Liability Act no substance listed
CAA – Clean Air Act CAA Substances listed:	no substance listed
CWA – Clean Water Act CWA Substances listed:	no substance listed
USA - state specific regulations	
California Proposition 65 Substance(s) listed under California Propos Titanium Dioxide Silica Sand Massachusetts right to know	ition 65 listed as carcinogen listed as carcinogen
Substance(s) listed under Massachusetts R Portland cement Titanium dioxide Calcium sulfate Silica Sand	light to Know;
Pennsylvania Right to know Substance(s) listed under Pennsylvania Rig Portland cement Titanium dioxide Calcium sulfate Silica Sand	ght to Know;
New Jersey Right to know Substance(s) listed under New Jersey Righ Portland cement Titanium dioxide Calcium sulfate Silica Sand	t to Know;
Section 16 Other Informa	tion

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.



NFPA Special Risk: NONE

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Cause serious eye damage.
H335	May cause respiratory irritation.
H350A	May cause cancer if inhaled
H372A	Causes damage to organs through prolonged or repeated exposure if inhaled

The information provided in this (Material) Safety Data Sheet represents a compilation of data drawn directly from various sources available to us. Texrite makes no representation or guarantee as to the suitability of this information to a particular application of the substance covered in the (Material) Safety Data Sheet.

Glossary

0.0000	5
ACGIH	-American Conference of Governmental
	Industrial Hygienists
CAS	-Chemical Abstract Service Number
CERCLA	A -Comprehensive Environmental Response,
	Compensation, and Liability Act
DOT	-U.S. Department of Transportation
IARC	-International Agency for Research on
	Cancer

- N/A -Not Available
- NTP -National Toxicology Program

- OSHA -Occupational Safety and Health Administration
- PEL -Permissible Exposure Limit
- ppm -Parts per million
- RCRA -Resource Conservation and Recovery Act
- SARA -Superfund Amendments and Reauthorization
- TLV -Threshold Limit Value
- TSCA -Toxic Substances Control Act
- IDLH -Immediately dangerous to life and health