2" SURFACE INDICATOR LOUVER







LANDSCAPE LIGHTING



Fixture Type:	
Catalog Number:	
Project:	
Location:	





PRODUCT DESCRIPTION

LED Landscape surface mount indicator luminaire for both soft and hard ground applications. The indicator light is perfect for outdoor applications, including wells and ponds, decks and patios, inground, as well as ceiling and wall applications.

FEATURES

- Slim low profile design-surface mount installation
- IP68 rated, Suitable for continuous immersion under water
- · Factory sealed water tight fi xtures
- · Solid stainless steel construction
- 10' lead wire and direct burial gel filled wire nuts included
- · Maintains constant lumen output against voltage drop
- UL 1838 Listed
- MLV dimmable with remote MLV dimmer

ORDERING NUMBER

	Color Temp	Finish
2511 Louver	27 2700K 30 3000K	BS Bronzed Stainless Steel SS Stainless Steel

2511-30

Example: 2511-30SS

SPECIFICATIONS

Input: 9 - 15VAC (Transformer is required)

Power: 2.8W / 3.2 VA
Brightness: 60lm
Beam Angle: 90°
CRI: 85

Rated Life: 60,000 hours

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

2" SURFACE INDICATOR LOUVER





Magnetic Transformers



Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS 75W Max

9150-TRN-SS 150W Max

9300-TRN-SS 300W Max

9600-TRN-SS 600W Max